

Frosta 480



Frosta is an elegantly designed decorative luminaire for ceilings and walls. It is suitable for homes as well as hotels, restaurants, etc. The diffuser provides a perfectly even light distribution with an aura of light in the ceiling. Easy installation with holes to fit all know ceiling boxes. For concealed or visible cabling. Dimmable with phasecut and DALI / push. Light levels can also be adjusted with dip switches on the driver. A pendant kit is sold separately, and fits both the phasecut and DALI / push version.

Frosta 480



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>211700 Frosta 480 White 2130lm 2700K Ra>80 Trailing edge 15W LED 142 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 117°, Direct/Indirect 92/8%, Acrylic diffuser</p>	Class II IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	Ø480 x H90
 <p>211707 Frosta 480 White 3860lm 3000K Ra>80 DALI-2 / Push Dim 26W LED 148 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 117°, Direct/Indirect 92/8%, Acrylic diffuser</p>	Class II IP20 IK08	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø480 x H90
 <p>211713 Frosta 480 White 2220lm 3000K Ra>80 Sensor Dim 15W LED 148 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 117°, Direct/Indirect 92/8%, Acrylic diffuser</p>	Class II IP20 IK08	Sensor Dim	Surface, Indoor Screwless terminal block	Ø480 x H90
 <p>211701 Frosta 480 White 2220lm 3000K Ra>80 Trailing edge 15W LED 148 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 117°, Direct/Indirect 92/8%, Acrylic diffuser</p>	Class II IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	Ø480 x H90
 <p>211708 Frosta 480 White 3220lm 4000K Ra>80 DALI-2 / Push Dim 24W LED 134 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 117°, Direct/Indirect 92/8%, Acrylic diffuser</p>	Class II IP20 IK08	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø480 x H90
 <p>211702 Frosta 480 White 2270lm 4000K Ra>80 Trailing edge 15W LED</p>	Class II IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	Ø480 x H90
Accessories	151 lm/W SDCM:3			

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
L80/B10>100,000, L90>60,000 Beam: 17°, Direct Indirect 92/8%, Acrylic diffuser  606093 Disc/Frosta Black Pendant Adapter				L5000 x W102 x H22
 606094 Disc/Frosta White Pendant Adapter				L5000 x W102 x H22