

Frosta 330



Frosta is an elegantly designed decorative luminaire for ceilings and walls. It is suitable for homes as well as hotels, restaurants, etc. The diffuser provides a perfectly even light distribution with an aura of light in the ceiling. Easy installation with holes to fit all know ceiling boxes. For concealed or visible cabling. Dimmable with phasecut and DALI / push. Light levels can also be adjusted with dip switches on the driver. A pendant kit is sold separately, and fits both the phasecut and DALI / push version.

Frosta 330



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>211733 Frosta 330 White 2120lm 2700K Ra>80 DALI-2 17W LED 125 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	DALI-2	Surface, Indoor Screwless terminal block	Ø330 x H77
 <p>211736 • Frosta 330 White Sensor Dim 2120lm 2700K Ra>80 Sensor Dim 17W LED 125 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	Sensor Dim	Surface, Indoor Screwless terminal block	Ø330 x H77
 <p>211730 Frosta 330 White 2120lm 2700K Ra>80 Trailing edge 17W LED 125 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	Trailing edge	Surface, Indoor Screwless terminal block	Ø330 x H77
 <p>211734 Frosta 330 White 2230lm 3000K Ra>80 DALI-2 17W LED 131 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	DALI-2	Surface, Indoor Screwless terminal block	Ø330 x H77
 <p>211737 Frosta 330 White Sensor Dim 2230lm 3000K Ra>80 Sensor Dim 17W LED 131 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	Sensor Dim	Surface, Indoor Screwless terminal block	Ø330 x H77
 <p>211731 Frosta 330 White 2230lm 3000K Ra>80 Trailing edge 17W LED 131 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	Trailing edge	Surface, Indoor Screwless terminal block	Ø330 x H77

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>211735 Frosta 330 White 2370lm 4000K Ra>80 DALI-2 17W LED 139 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	DALI-2	Surface, Indoor Screwless terminal block	Ø330 x H77
 <p>211738 • Frosta 330 White Sensor Dim 2370lm 4000K Ra>80 Sensor Dim 17W LED 139 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	Sensor Dim	Surface, Indoor Screwless terminal block	Ø330 x H77
 <p>211732 Frosta 330 White 2370lm 4000K Ra>80 Trailing edge 17W LED 139 lm/W SDCM:3 L80/B10>100,000, L90>60,000 Beam: 125°, Direct, Acrylic diffuser</p>	Class II IP20 IK04	Trailing edge	Surface, Indoor Screwless terminal block	Ø330 x H77
Accessories				
 <p>606095 Disc/Frosta Black Pendant Adapter</p>				L5000 x W102 x H22
 <p>606094 Disc/Frosta White Pendant Adapter</p>				L5000 x W102 x H22

• = This article is produced by order, with an expected delivery time of 3-4 weeks.