








Kjevik is a solid bollard for public spaces, paths and parks. It has a very high lumen output, with low energy consumption. The light distribution is wide and precise with all the light below the horizontal plane, therefore no light pollution in a safe and glare-free environment. Classic design blends in with all surroundings. A 180°-degree shield is available as accessory and is perfect for paths or other places where light should be restricted to a semi-circle.

Product- and environment images



Article codes



| Article | | Protection | Control gear | Mounting/Connection | Dimensions |
|---|--|-----------------|--------------|---------------------|------------------------------|
|  | 623801 [•] | Class II | DALI-2 | Outdoor | Ø200 x H1010 |
| | Kjevik Black 2060lm 3000K Ra>80 | IP66 | | | |
| | DALI-2 | IK10 | | | |
| | 26W LED | | | | |
| | 79 lm/W SDCM:2 L90/B10>100,000 Direct, | | | | |
|  | 623800 | Class II | On/Off | Outdoor | Ø200 x H1010 |
| | Kjevik Black 2060lm 3000K Ra>80 | IP66 | | | |
| | On/Off | IK10 | | | |
| | 26W LED | | | | |
| | 79 lm/W SDCM:2 L90/B10>100,000 Direct, | | | | |
| Accessories | | | | | |
|  | 623804 | | | | L178 x W89 x H112 |
| | Kjevik Black 180° Diffuser | | | | |
|  | 8249042067 | | | | Ø155 x L248 x W108 x H450 |
| | Ground anchor | | | | |
|  | 8249042070 | | | | Ø155 x H450 |
| | Ground anchor f/'Cetong' | | | | |

[•] = This article is produced by order, with an expected delivery time of 3-4 weeks.