

# Inspire R TW



Inspire R TW is a rectangular recessed downlight for indoor use. With cubist black reflectors it has very low glare and harmonious non-flickering light with a well-defined light pattern. Inspire R TW is suitable for use in high-end residential and commercial environments. Tunable White from 2000-4000K or 2700-6500K. Controlled by TW LEDDim or DALI Type 8 (DALI Type 8 only version 300).

# Inspire R TW



## Product- and environment images



# Article codes



| Article   | Protection                          | Control gear   | Mounting/Connection   | Dimensions       |
|---|-------------------------------------|----------------|---|------------------|
|  <p>212446<br/> <b>Inspire R Black 300 970lm (@4000K)</b><br/> <b>2000-4000K Ra&gt;90 TW DALI Type 8</b><br/> <b>17W LED</b><br/>                     57 lm/W SDCM:2<br/>                     L90/B10&gt;100,000<br/>                     Beam: 55°, Direct, Lens</p>               | <b>Class II SELV</b><br><b>IP20</b> | TW DALI Type 8 | Recessed, Indoor<br>5 pol Linect / screwless terminal block | L303 x W62 x H40 |
|  <p>212440<br/> <b>Inspire R Black 150 500lm (@4000K)</b><br/> <b>2000-4000K Ra&gt;90 TW LEDDim</b><br/> <b>10W LED</b><br/>                     50 lm/W SDCM:2<br/>                     L90/B10&gt;100,000<br/>                     Beam: 55°, Direct, Lens</p>                   | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L163 x W62 x H40 |
|  <p>212442<br/> <b>Inspire R Black 300 970lm (@4000K)</b><br/> <b>2000-4000K Ra&gt;90 TW LEDDim</b><br/> <b>17W LED</b><br/>                     57 lm/W SDCM:2<br/>                     L90/B10&gt;100,000<br/>                     Beam: 55°, Direct, Lens</p>                    | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L303 x W62 x H40 |
|  <p>212445<br/> <b>Inspire R White 300 970lm</b><br/> <b>(@4000K) 2000-4000K Ra&gt;90 TW</b><br/> <b>DALI Type 8</b><br/> <b>17W LED</b><br/>                     57 lm/W SDCM:2<br/>                     L90/B10&gt;100,000<br/>                     Beam: 55°, Direct, Lens</p> | <b>Class II SELV</b><br><b>IP20</b> | TW DALI Type 8 | Recessed, Indoor<br>5 pol Linect / screwless terminal block | L303 x W62 x H40 |
|  <p>212439<br/> <b>Inspire R White 150 500lm</b><br/> <b>(@4000K) 2000-4000K Ra&gt;90 TW</b><br/> <b>LEDDim</b><br/> <b>10W LED</b><br/>                     50 lm/W SDCM:2<br/>                     L90/B10&gt;100,000<br/>                     Beam: 55°, Direct, Lens</p>     | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L163 x W62 x H40 |
|  <p>212441<br/> <b>Inspire R White 300 970lm</b><br/> <b>(@4000K) 2000-4000K Ra&gt;90 TW</b><br/> <b>LEDDim</b><br/> <b>17W LED</b><br/>                     57 lm/W SDCM:2<br/>                     L90/B10&gt;100,000<br/>                     Beam: 55°, Direct, Lens</p>      | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L303 x W62 x H40 |

# Article codes



| Article   | Protection                          | Control gear   | Mounting/Connection   | Dimensions       |
|---|-------------------------------------|----------------|---|------------------|
|  <p>212453<br/> <b>Inspire R Black 300 1080lm</b><br/>           (@6500K) 2700-6500K Ra&gt;90 TW<br/> <b>DALI Type 8</b><br/> <b>17W LED</b><br/>           64 lm/W SDCM:2<br/>           L90/B10&gt;100,000<br/>           Beam: 55°, Direct, Lens</p>   | <b>Class II SELV</b><br><b>IP20</b> | TW DALI Type 8 | Recessed, Indoor<br>5 pol Linect / screwless terminal block | L303 x W62 x H40 |
|  <p>212449<br/> <b>Inspire R Black 150 560lm</b> (@6500K)<br/> <b>2700-6500K Ra&gt;90 TW LEDDim</b><br/> <b>10W LED</b><br/>           56 lm/W SDCM:2<br/>           L90/B10&gt;100,000<br/>           Beam: 55°, Direct, Lens</p>                       | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L163 x W62 x H40 |
|  <p>212452<br/> <b>Inspire R Black 300 1080lm</b><br/>           (@6500K) 2700-6500K Ra&gt;90 TW<br/> <b>LEDDim</b><br/> <b>17W LED</b><br/>           64 lm/W SDCM:2<br/>           L90/B10&gt;100,000<br/>           Beam: 55°, Direct, Lens</p>        | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L303 x W62 x H40 |
|  <p>212451<br/> <b>Inspire R White 300 1080lm</b><br/>           (@6500K) 2700-6500K Ra&gt;90 TW<br/> <b>DALI Type 8</b><br/> <b>17W LED</b><br/>           64 lm/W SDCM:2<br/>           L90/B10&gt;100,000<br/>           Beam: 55°, Direct, Lens</p> | <b>Class II SELV</b><br><b>IP20</b> | TW DALI Type 8 | Recessed, Indoor<br>5 pol Linect / screwless terminal block | L303 x W62 x H40 |
|  <p>212448<br/> <b>Inspire R White 150 560lm</b><br/>           (@6500K) 2700-6500K Ra&gt;90 TW<br/> <b>LEDDim</b><br/> <b>10W LED</b><br/>           56 lm/W SDCM:2<br/>           L90/B10&gt;100,000<br/>           Beam: 55°, Direct, Lens</p>      | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L163 x W62 x H40 |
|  <p>212450<br/> <b>Inspire R White 300 1080lm</b><br/>           (@6500K) 2700-6500K Ra&gt;90 TW<br/> <b>LEDDim</b><br/> <b>17W LED</b><br/>           64 lm/W SDCM:2</p>   | <b>Class II SELV</b><br><b>IP20</b> | TW LEDDim      | Recessed, Indoor<br>Screwless terminal block                | L303 x W62 x H40 |
| <b>Accessories</b>  |                                     |                |   |                  |

# Article codes



| Article  | L90/B10>100,000 | Protection | Control gear | Mounting/Connection | Dimensions       |
|--|-----------------|------------|--------------|---------------------|------------------|
|  Beam: 55°, Direct lens | 212482          |            |              |                     | L140 x W38 x H16 |
|                          | 212483          |            |              |                     | L280 x W38 x H16 |
|                         | 212480          |            |              |                     | L140 x W38 x H16 |
|                          | 212481          |            |              |                     | L280 x W38 x H16 |
|                          | 820090          |            |              |                     | L250 x W13 x H13 |
|                         | 8246094364      |            |              |                     | L270 x W75 x H35 |
|                        | 8246094500      |            |              |                     | L270 x W75 x H35 |