

Rax Soft 200 TW



Rax Soft 200 TW is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with satin matt reflector for high efficiency. Rax Soft 200 TW is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm. Tunable White 2700-6500K LED Dim or DALI Type 8.

Rax Soft 200 TW




Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212577 Rax Soft 200 Satin 2700-6500K Ra>80 TW DALI Type 8 28W LED 93 lm/W SDCM:3 L90/B10>100,000 Beam: 62°, Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	TW DALI Type 8	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø216 x H93
 <p>212576 Rax Soft 200 Satin TW LEDDim 2700-6500K Ra>80 TW LEDDim 28W LED 93 lm/W SDCM:3 L90/B10>100,000 Beam: 62°, Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	TW LEDDim	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
Accessories				
 <p>212618 Rax 200 Black Rehabring Ø205-250mm</p>				Ø270 x H16
 <p>212619 Rax 200 Black Rehabring Ø210-280mm</p>				Ø300 x H16
 <p>212625 Rax 200 Black Glass clear IP44</p>				Ø218 x H12
 <p>212627 Rax 200 Black Glass frosted IP44</p>				Ø220 x H12
 <p>212624 Rax 200 White Glass clear IP44</p>				Ø218 x H12
 <p>212626 Rax 200 White Glass frosted IP44</p>				Ø218 x H12
 <p>8249044696 Rax 200 White Rehabring Ø205-250mm</p>				Ø270 x H16

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 900109 Reliefplate				L400 x W400 x H1
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35
 8249038725 Rax 200 Mounting plate				L585 x W260 x H15