

Fevik 1000/2000 + 1500/2500



Fevik is a modern LED luminaire with a slim profile and wide light dispersion, for wall mounting. During installation, the light output is selected from a choice of two levels using a dipswitch on the LED module. The luminaire is made of die-cast aluminium, powder-coated white or graphite, with an aluminium reflector and a tempered glass diffuser. Fevik can be mounted as an upward light or a downward light. With the adjustable wall/corner bracket and ArmMount (accessory), Fevik can be used in most lighting situations. The wall/corner bracket can be angled 180° for wall mounting, and 165° for corners. Using ArmMount, Fevik can be installed on horizontal tubes. Fits Ø42–48 mm tubes and provides an invisible transition between luminaire and wall bracket.

Fevik 1000/2000 + 1500/2500



Product- and environment images



Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|---|---|---------------|--|--------------------|
|  <p>623253 Fevik Graphite 1000/2000 3000K Ra>80 Trailing edge LED 99/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Direct, Reflector</p> | Class II IP65 IK10 | Trailing edge | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |
|  <p>623260 Fevik Graphite 1500/2500 3000K Ra>80 Trailing edge LED 100/89lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Direct, Reflector</p> | Class II IP65 IK10 | Trailing edge | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |
|  <p>623255 Fevik Graphite 1000/2000 3000K Ra>80 Twilight LED 99/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Direct, Reflector</p> | Class II IP65 IK10 | Twilight | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |
|  <p>623257 Fevik White 1000/2000 3000K Ra>80 Trailing edge LED 99/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Direct, Reflector</p> | Class II IP65 IK10 | Trailing edge | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |
|  <p>623254 Fevik Graphite 1000/2000 4000K Ra>80 Trailing edge LED 106/102lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Direct, Reflector</p> | Class II IP65 IK10 | Trailing edge | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |
|  <p>623261 Fevik Graphite 1500/2500 4000K Ra>80 Trailing edge LED 108/96lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Direct, Reflector</p> | Class II IP65 IK10 | Trailing edge | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |

Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|---|---------------|--|--------------------|
|  <p>623258 Fevik White 1000/2000 4000K Ra>80 Trailing edge LED 106/102lm/W SDCM:3 L80/B20>50,000 Beam: 100°, Direct, Reflector</p> | Class II IP65 IK10 | Trailing edge | Surface, Outdoor Screwless terminal block | W223 x H110 x D276 |
| Accessories | | | | |
|  <p>623247 Fevik Armmount Graphite</p> | | | | W130 x H130 x D240 |
|  <p>623248 Fevik Graphite Pole bracket</p> | | | | L225 x W105 x H111 |
|  <p>623249 Fevik Graphite Wall and corner bracket</p> | | | | W220 x H100 x D135 |
|  <p>600001 Number Plate 220x170mm</p> | | | Indoor / Outdoor | L220 x W170 x H10 |