



DALI three-phase rail spot with integrated powerful LED chip and driver. Mounted using DALI global multi-adapter, which is ideal for SG's DALI three-phase rail system (Shopline DALI) as well as other systems where Global DALI can be used. Zip Pro DALI is made of powder-coated aluminium, flexible and able to be pointed in almost all directions, making it the obvious choice for shops and exhibitions.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	320732 Zip Pro 3-Circuit Black 3370lm 3000K Ra>90 DALI-2 40W LED 84 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector	Class I IP20	DALI-2	Surface, Indoor ShopLine DALI track (adapter included)	Ø100 x L218 x W100 x H148
	320730 Zip Pro 3-Circuit White 3470lm 3000K Ra>90 DALI-2 40W LED 87 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector	Class I IP20	DALI-2	Surface, Indoor ShopLine DALI track (adapter included)	Ø100 x L218 x W100 x H148
	320733 Zip Pro 3-Circuit Black 3610lm 4000K Ra>90 DALI-2 40W LED 90 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector	Class I IP20	DALI-2	Surface, Indoor ShopLine DALI track (adapter included)	Ø100 x L218 x W100 x H148
	320731 Zip Pro 3-Circuit White 3710lm 4000K Ra>90 DALI-2 40W LED 93 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector	Class I IP20	DALI-2	Surface, Indoor ShopLine DALI track (adapter included)	Ø100 x L218 x W100 x H148
Accessories					
	312531 Shopline DALI Black Monopoint	Class I IP20		Surface, Indoor	Ø143 x H35
	312530 Shopline DALI White Monopoint	Class I IP20		Surface, Indoor	Ø143 x H35