

Disc 760



Disc 760 is suitable for large rooms, foyers, meeting rooms, restaurants, etc. Energy-efficient surface LED luminaires with a slim profile for a contemporary look. The Opalprismatic diffuser provides uniform light with low glare, UGR

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 606178 Disc 760 Black 6230/6330lm 2700/3000K Ra>80 DALI-2 / Push Dim 55W LED 113 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 83°, Direct, Opalprism	Class II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø760 x H55
 606177 Disc 760 White 6910/7130lm 2700/3000K Ra>80 DALI-2 / Push Dim 55W LED 126 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 88°, Direct, Opalprism	Class II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø760 x H55
 606133 Disc 760 Black 7360lm 4000K Ra>80 DALI-2 / Push Dim 64W LED 115 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 83°, Direct, Opalprism	Class II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø760 x H55
 606131 Disc 760 White 7540lm 4000K Ra>80 DALI-2 / Push Dim 64W LED 118 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 88°, Direct, Opalprism	Class II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø760 x H55
Accessories				
 616113 Disc 760 Black Pendantkit				L5000 x W102 x H22
 616112 Disc 760 White Pendantkit				L5000 x W102 x H22
 212234 Sense Surface/Disc 760 2m Wire kit				L2000