

Tysnes 66



Tysnes 66 is a tri-proof luminaire for garages, storage rooms and production facilities. It has low power consumption, high lumen output and long lifetime. It can easily be mounted on ceilings with clips or suspended in wires. Sturdy steel clips attached to the luminaire holds the diffuser. It has cable entries in both ends and weakening for cabling from the back. Tysnes 66 comes in 3 lengths and has dip switches on the driver that allows setting the required light level. Also available as emergency light, with a 3-hour battery pack.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 120072 Tysnes 66 1500 Grey 6720lm 3000K Ra>80 DALI-2 43W LED 156 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm ² through wiring	L1500 x W85 x H80
 120064 Tysnes 66 1200 Grey 5480lm 3000K Ra>80 On/Off 35W LED 157 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	On/Off	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1200 x W85 x H80
 120065 Tysnes 66 1500 Grey 6720lm 3000K Ra>80 On/Off 43W LED 156 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	On/Off	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1500 x W85 x H80
 120037 Tysnes 66 1500 Grey 6400lm 4000K Ra>80 DALI-2 40W LED 160 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm ² through wiring	L1500 x W85 x H80
 120038 Tysnes 66 650 Grey 2060lm 4000K Ra>80 DALI-2 14W LED 147 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 121°, Direct, Opal	Class I IP66 IK10	DALI-2	Surface, Indoor Screwless terminal block	L650 x W85 x H80
 120039 Tysnes 66 1200 Grey 5510lm 4000K Ra>80 DALI-2 34W LED 162 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm ² through wiring	L1200 x W85 x H80

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 120030 Tysnes 66 650 Grey 2060lm 4000K Ra>80 On/Off 14W LED 147 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 121°, Direct, Opal	Class I IP66 IK10	On/Off	Surface, Indoor Screwless terminal block	L650 x W85 x H80
 120031 Tysnes 66 1200 Grey 5510lm 4000K Ra>80 On/Off 34W LED 162 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	On/Off	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm² through wiring	L1200 x W85 x H80
 120032 Tysnes 66 1500 Grey 6400lm 4000K Ra>80 On/Off 40W LED 160 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	On/Off	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm² through wiring	L1500 x W85 x H80
 120035 Tysnes 66 1200 Grey 5510lm 4000K Ra>80 Sensor 34W LED 162 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	Sensor	Surface, Indoor 5-pole screwless terminal block with 3x2,5mm² and 2x1,5mm² through wiring	L1200 x W85 x H80
 120036 Tysnes 66 1500 Grey 6400lm 4000K Ra>80 Sensor 40W LED 160 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 117°, Direct, Opal	Class I IP66 IK10	Sensor	Surface, Indoor 5-pole screwless terminal block with 3x2,5mm² and 2x1,5mm² through wiring	L1500 x W85 x H80
Accessories				
 120063 Tysnes 66 45° Fastening				L45 x W43 x H43
 8249044900 Wirekit 2x5m				L19 x W25 x H150



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249044913 Mounting kit for adjustable angulation				L100 x W98 x H95