

Sense IP65 Eco



Sense IP65 Eco is a waterproof luminaire with opal prismatic front, delivered complete with driver. Ideal for industrial kitchens, hospitals, laboratories, and production facilities. Very low glare, UGR

Sense IP65 Eco



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212468 Sense IP65 Eco White 4060lm 3000K Ra>80 DALI-2 34W LED 119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprism</p>	Class II IP65	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L597 x W597 x H53
 <p>212390 Sense IP65 Eco White 4060lm 3000K Ra>80 Trailing edge 34W LED 119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprism</p>	Class II IP65	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	L597 x W597 x H53
 <p>212414 Sense IP65 Eco White 4350lm 4000K Ra>80 DALI-2 34W LED 128 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprism</p>	Class II IP65	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L597 x W597 x H53
 <p>212391 Sense IP65 Eco White 4350lm 4000K Ra>80 Trailing edge 34W LED 128 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprism</p>	Class II IP65	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	L597 x W597 x H53
Accessories				
 <p>212936 Sense 600x600 Black Plaster board/Troldtekt Recessed frame</p>				L640 x W640 x H50
 <p>820489 Sensor Dim Box White 200VA</p>				L220 x W75 x H34
 <p>8249044557 625x625 White Plaster board/Troldtekt Recessed frame</p>				L625 x W625 x H55
 <p>8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</p>				L270 x W75 x H35

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35