Fagernes Bollard





A modern, classic bollard. A perfect match with Fagernes wall lamps. It gives a great, glare free light and is ideal for driveways, gardens and other outdoor environments. Fitted with an efficient integrated LED and is phasecut dimmable. Can be screwed directly on the surface or be cast in with an anchoring set (sold separately). It features an innovative adjustment mechanism, allowing the adjustment to be done from the top side. Fagernes bollard is also available in a version with outlet. Very handy for all things that need power in the garden. It also comes with a daylight and motion sensor (PIR). After dark it switches on when it detects movement, and stays on for the pre-set time. A good way of saving power and preventing light pollution. It can also control the light of other luminaires (slaves). A shield plate is available as accessory, which can be clicked on to block off the light in one or more directions as desired.

Fagernes Bollard



Product- and environment images







Article codes



ticle		Protection	Control gear	Mounting/Connection	Dimensions
	630067 °	Class I	PIR Sensor	Onto surfaces or ground anchor,	L200 x W200 x H800
ı	Fagernes Bollard Black 270lm	IP44		Outdoor	
	2700K Ra>80 PIR Sensor	IK08		Screwless terminal block	
	9W LED				
	30 lm/W SDCM:3				
	L70/B50>100,000, L90/B10>50,000				
	Beam: 94,2°, Indirect,				
	630064	Class II	Trailing edge	Onto surfaces or ground anchor,	L200 x W200 x H800
	Fagernes Bollard Black 270lm	IP44		Outdoor	
	2700K Ra>80 Trailing edge	IK08		Screwless terminal block	
	9W LED				
	30 lm/W SDCM:3				
	L70/B50>100,000, L90/B10>50,000				
	Beam: 94,2°, Indirect,				
	630065	Class I	Trailing edge	Onto surfaces or ground anchor,	L200 x W200 x H800
I	Fagernes Bollard Black w/ outlet	IP44		Outdoor	
	270lm 2700K Ra>80 Trailing edge	IK08		Screwless terminal block	
	9W LED				
	30 lm/W SDCM:3				
	L70/B50>100,000, L90/B10>50,000				
	Beam: 94,2°, Indirect,				
ot released yet	630104 •	Class I	PIR Sensor	Onto surfaces or ground anchor,	L200 x W200 x H800
n released yet	Fagernes Bollard Black 610lm	IP44		Outdoor	
	3000K Ra>80 PIR Sensor	IK08		Screwless terminal block	
	12W LED				
	51 lm/W SDCM:3				
	L70/B50>100,000				
	Beam: 94,2°, Indirect, Glass Clear				
Ш	630102	Class II	Trailing edge	Onto surfaces or ground anchor,	L200 x W200 x H800
	Fagernes Bollard Black 610lm	IP44		Outdoor	
•	3000K Ra>80 Trailing edge	IK08		Screwless terminal block	
	12W LED				
	51 lm/W SDCM:3				
	L70/B50>100,000				
	Beam: 94,2°, Indirect, Glass Clear				
	630103	Class I	Trailing edge	Onto surfaces or ground anchor,	L200 x W200 x H800
	Fagernes Bollard Black w/ outlet	IP44		Outdoor	
	610lm 3000K Ra>80 Trailing edge	IK08		Screwless terminal block	
	12W LED				
	51 lm/W SDCM:3				
	L70/B50>100,000				

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	630076 Fagernes Bollard Black Cover				L139 x W115 x H11
M	630066 Fagernes Bollard Anchoring set				L194 x W194 x H223

^{• =} This article is produced by order, with an expected delivery time of 3-4 weeks.