



StripLine is a flexible LED strip system designed to provide architectural lighting on ceilings and walls, in niches and cabinets, and is suitable for both indoor and outdoor use. StripLine RGBW allows you to create all the colours of the rainbow by mixing red, green and blue (RGB) in different ways. It also features pure white (W). StripLine RGBW requires a driver and controller in order to operate correctly. To control the controller (the light), you can use a handy remote control and/or pulse switch. The LED strip is encapsulated to an IP54 rating, and is supplied with mounting tape on the rear and connection cables already fully fitted. The LED strip must be fitted in one of the available StripLine aluminium profiles for surface-mounted, corner, recessed or frameless installations. It can also be used independently in indoor settings. The profiles are supplied with a solid polycarbonate front diffuser that can be easily attached and removed. The front diffuser is also supplied as a roll, providing the option of very long, continuous fronts. (The diffuser on roll and the Round Diffuser are not compatible with the Slim and Soft profiles). Different driver kits are available, dimmable with phase-cut or push dim. Driver kits come complete with screwless terminal block for looping. The drivers are encapsulated to an IP20 rating. StripLine RGBW can be cut at intervals of 7.1 cm to be tailored to each individual installation. When cutting, silicone should be applied to maintain water protection.

# StripLine RGBW



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
391452 <b>StripLine 5m 790lm/m RGBW (3000K) Ra&gt;90</b> <b>LED</b> SDCM:3 L70/B50>50,000 Beam: 120°, Direct,	<b>Class III</b> <b>IP54</b>		Surface, Indoor / Outdoor Cable 2x2m	L5000 x W12 x H3.2
391479 <b>StripLine 10m 790lm/m RGBW (3000K) Ra&gt;90</b> <b>LED</b> SDCM:3 L70/B50>50,000 Beam: 120°, Direct,	<b>Class III</b> <b>IP54</b>		Surface, Indoor / Outdoor Cable 2x2m	L10000 x W12 x H3.2
<b>Drivers</b>				
820444 <b>IP65 Junction box Black Incl driver 90W Trailing edge</b>				L346 x W127 x H53
820440 <b>SG White Driver 24V 36W Trailing edge</b>				L200 x W85 x H35
820441 <b>SG White Driver 24V 75W Trailing edge</b>				L200 x W85 x H35
820442 <b>SG White Driver 24V 150W Trailing edge</b>				L310 x W85 x H35
<b>Accessories</b>				
391457 <b>Remote Control Black RF RGBW</b>				L139 x W36 x H11
391455 <b>Controller White RF RGBW Remote Control RF / Push Dim</b>				L175 x W45 x H27
820483 <b>LEDDim Smart Color Controller White SG Smart/ Remote Control RF * / Push Dim</b>				L175 x W45 x H27