



EcoLine is a slim and stylish ceiling luminaire suitable for use in offices, schools and public buildings. Designed for quick and easy installation. Three-layer optical system with low glare: UGR

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212802 EcoLine 1600 White 4880lm 3000K Ra>80 DALI-2 36W LED 136 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	DALI-2	Suspended or surface, Indoor 3+2 pole Screwless terminal block	L1600 x W166 x H47
 212093 EcoLine 1200 White 3910lm 3000K Ra>80 DALI-2 / Push Dim 30W LED 130 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	DALI-2 / Push Dim	Suspended or surface, Indoor 3+2 pole Screwless terminal block	L1235 x W166 x H47
 212091 EcoLine 1200 White 3910lm 3000K Ra>80 On/Off 30W LED 130 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	On/Off	Suspended or surface, Indoor 3 pole Screwless terminal block	L1235 x W166 x H47
 212800 EcoLine 1600 White 4880lm 3000K Ra>80 On/Off 36W LED 136 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	On/Off	Suspended or surface, Indoor 3 pole Screwless terminal block	L1600 x W166 x H47
 212803 EcoLine 1600 White 5180lm 4000K Ra>80 DALI-2 36W LED 144 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	DALI-2	Suspended or surface, Indoor 3+2 pole Screwless terminal block	L1600 x W166 x H47
 212094 EcoLine 1200 White 4150lm 4000K Ra>80 DALI-2 / Push Dim 30W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	DALI-2 / Push Dim	Suspended or surface, Indoor 3+2 pole Screwless terminal block	L1235 x W166 x H47

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212092 EcoLine 1200 White 4150lm 4000K Ra>80 On/Off 30W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	On/Off	Suspended or surface, Indoor 3 pole Screwless terminal block	L1235 x W166 x H47
 212801 EcoLine 1600 White 5180lm 4000K Ra>80 On/Off 36W LED 144 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprism	Class I IP20	On/Off	Suspended or surface, Indoor 3 pole Screwless terminal block	L1600 x W166 x H47
Accessories				
 212255 T-profil White Suspension Rail 600mm				L596 x W35 x H17
 212095 EcoLine 2m Wire kit				L2000