Arlon Round

Arlon Round is a slim, stylish wall luminaire with retracted, slightly angled light source. Suitable for spaces such as walkways and corridors. Highly efficient with high lumens per Watt. Can be dimmed using trailing edge dimming or DALI dimmer (DALI upon request). Easy installation with back plate for mounting, two cable inputs and a quick connector. Made from high quality die-cast, powder-coated aluminium. Arlon Round can also be mounted on bollards.

Arlon Round

sg

Product- and environment images

Article codes

Article		Protection	Control gear	Mounting/Connection	Dimensions
	653600 **Arlon Round Black 790lm 2700K** **Ra>80 Trailing edge** **10W LED** 79 lm/W SDCM:3 L80/B20>100,000 Direct, Difuser	**Class II** **IP65** **IK10**	Trailing edge	Wall, Outdoor Screwless terminal block	L269 x W266 x H47
	653617 **Arlon Round Corten 810lm 2700K** **Ra>80 Trailing edge** **10W LED** 81 lm/W SDCM:3 L80/B20>100,000 Direct, Difuser	**Class II** **IP65** **IK10**	Trailing edge	Wall, Outdoor Screwless terminal block	L269 x W266 x H47
	653602 **Arlon Round White 1050lm 2700K** **Ra>80 Trailing edge** **10W LED** 105 lm/W SDCM:3 L80/B20>100,000 Direct, Difuser	**Class II** **IP65** **IK10**	Trailing edge	Wall, Outdoor Screwless terminal block	L269 x W266 x H47
	653601 **Arlon Round Black 840lm 3000K** **Ra>80 Trailing edge** **10W LED** 84 lm/W SDCM:3 L80/B20>100,000 Direct, Difuser	**Class II** **IP65** **IK10**	Trailing edge	Wall, Outdoor Screwless terminal block	L269 x W266 x H47
	653618 **Arlon Round Corten 860lm 3000K** **Ra>80 Trailing edge** **10W LED** 86 lm/W SDCM:3 L80/B20>100,000 Direct, Difuser	**Class II** **IP65** **IK10**	Trailing edge	Wall, Outdoor Screwless terminal block	L269 x W266 x H47
	653603 **Arlon Round White 1120lm 3000K** **Ra>80 Trailing edge** **10W LED** 112 lm/W SDCM:3 L80/B20>100,000 Direct, Difuser	**Class II** **IP65** **IK10**	Trailing edge	Wall, Outdoor Screwless terminal block	L269 x W266 x H47

Article codes

Article		Protection	Control gear	Mounting/Connection	Dimensions
	653623	**Class II**	Trailing edge	Wall, Outdoor	L269 x W266 x H47
	Arlon Round Black 890lm 4000K	**IP65**		Screwless terminal block	
	Ra>80 Trailing edge	**IK10**			
	10W LED				
	89 lm/W SDCM:3				
	L80/B20>100,000				
	Direct, Difuser				

Accessories

	614580				L1000 x W290 x H220
	Bollard Solo, Tanto, Uno, Primo and Arlon Round Black				
	653616				L248 x W175 x H15
	Arlon Round Black Bollard bracket				
	600580				W330 x H524 x D260
	Bollard Solo, Tanto, Uno, Primo and Arlon Round Anchoring set				