

# Hurdal



Hurdal is a highly efficient surface mounted luminaire for a wide variety of applications. It is easily installed directly in the ceiling or on the wall and has cable entrance in both ends in addition to two in the center. The luminaire is IP44 with steel base and aluminium end caps. Hurdal is available in three lengths. Dip switches makes it possible to adjust the light level.

## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>113112  <b>Hurdal 600 White 1590lm 3000K</b>  <b>Ra&gt;80 DALI-2</b>  <b>12W LED</b>                      133 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L600 x W72 x H76
 <p>113113  <b>Hurdal 1200 White 3460lm 3000K</b>  <b>Ra&gt;80 DALI-2</b>  <b>24W LED</b>                      144 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1200 x W72 x H76
 <p>113114  <b>Hurdal 1500 White 4640lm 3000K</b>  <b>Ra&gt;80 DALI-2</b>  <b>31W LED</b>                      150 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1500 x W72 x H76
 <p>113100  <b>Hurdal 600 White 1590lm 3000K</b>  <b>Ra&gt;80 On/Off</b>  <b>12W LED</b>                      133 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	On/Off	Surface, Indoor 3 pole Screwless terminal block	L600 x W72 x H76
 <p>113101  <b>Hurdal 1200 White 3460lm 3000K</b>  <b>Ra&gt;80 On/Off</b>  <b>24W LED</b>                      144 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	On/Off	Surface, Indoor 3 pole Screwless terminal block	L1200 x W72 x H76
 <p>113102  <b>Hurdal 1500 White 4640lm 3000K</b>  <b>Ra&gt;80 On/Off</b>  <b>31W LED</b>                      150 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	On/Off	Surface, Indoor 3 pole Screwless terminal block	L1500 x W72 x H76

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>113118  <b>Hurdal 600 White 1590lm 3000K</b>  <b>Ra&gt;80 PIR Sensor</b>  <b>12W LED</b>            133 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	PIR Sensor	Surface, Indoor 4-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring	L600 x W72 x H76
 <p>113119  <b>Hurdal 1200 White 3460lm 3000K</b>  <b>Ra&gt;80 PIR Sensor</b>  <b>24W LED</b>            144 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	PIR Sensor	Surface, Indoor 4-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring	L1200 x W72 x H76
 <p>113120  <b>Hurdal 1500 White 4640lm 3000K</b>  <b>Ra&gt;80 PIR Sensor</b>  <b>31W LED</b>            150 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	PIR Sensor	Surface, Indoor 4-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring	L1500 x W72 x H76
 <p>113106  <b>Hurdal 600 White 1590lm 3000K</b>  <b>Ra&gt;80 Sensor Dim</b>  <b>12W LED</b>            133 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	Sensor Dim	Surface, Indoor 6-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring+2x1,5mm <sup>2</sup> control	L600 x W72 x H76
 <p>113107  <b>Hurdal 1200 White 3460lm 3000K</b>  <b>Ra&gt;80 Sensor Dim</b>  <b>24W LED</b>            144 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	Sensor Dim	Surface, Indoor 6-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring+2x1,5mm <sup>2</sup> control	L1200 x W72 x H76
 <p>113108  <b>Hurdal 1500 White 4640lm 3000K</b>  <b>Ra&gt;80 Sensor Dim</b>  <b>31W LED</b>            150 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	Sensor Dim	Surface, Indoor 6-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring+2x1,5mm <sup>2</sup> control	L1500 x W72 x H76

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>113115  <b>Hurdal 600 White 1710lm 4000K</b>  <b>Ra&gt;80 DALI-2</b>  <b>12W LED</b>                      143 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L600 x W72 x H76
 <p>113116  <b>Hurdal 1200 White 3660lm 4000K</b>  <b>Ra&gt;80 DALI-2</b>  <b>24W LED</b>                      153 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1200 x W72 x H76
 <p>113117  <b>Hurdal 1500 White 4820lm 4000K</b>  <b>Ra&gt;80 DALI-2</b>  <b>31W LED</b>                      155 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	DALI-2	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1500 x W72 x H76
 <p>113103  <b>Hurdal 600 White 1710lm 4000K</b>  <b>Ra&gt;80 On/Off</b>  <b>12W LED</b>                      143 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	On/Off	Surface, Indoor 3 pole Screwless terminal block	L600 x W72 x H76
 <p>113104  <b>Hurdal 1200 White 3660lm 4000K</b>  <b>Ra&gt;80 On/Off</b>  <b>24W LED</b>                      153 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	On/Off	Surface, Indoor 3 pole Screwless terminal block	L1200 x W72 x H76
 <p>113105  <b>Hurdal 1500 White 4820lm 4000K</b>  <b>Ra&gt;80 On/Off</b>  <b>31W LED</b>                      155 lm/W SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	On/Off	Surface, Indoor 3 pole Screwless terminal block	L1500 x W72 x H76

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>113121  <b>Hurdal 600 White 1710lm 4000K</b>  <b>Ra&gt;80 PIR Sensor</b>  <b>12W LED</b>            143 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	PIR Sensor	Surface, Indoor 4-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring	L600 x W72 x H76
 <p>113122  <b>Hurdal 1200 White 3660lm 4000K</b>  <b>Ra&gt;80 PIR Sensor</b>  <b>24W LED</b>            153 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	PIR Sensor	Surface, Indoor 4-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring	L1200 x W72 x H76
 <p>113123  <b>Hurdal 1500 White 4820lm 4000K</b>  <b>Ra&gt;80 PIR Sensor</b>  <b>31W LED</b>            155 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	PIR Sensor	Surface, Indoor 4-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring	L1500 x W72 x H76
 <p>113109  <b>Hurdal 600 White 1710lm 4000K</b>  <b>Ra&gt;80 Sensor Dim</b>  <b>12W LED</b>            143 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	Sensor Dim	Surface, Indoor 6-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring+2x1,5mm <sup>2</sup> control	L600 x W72 x H76
 <p>113110  <b>Hurdal 1200 White 3660lm 4000K</b>  <b>Ra&gt;80 Sensor Dim</b>  <b>24W LED</b>            153 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	Sensor Dim	Surface, Indoor 6-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring+2x1,5mm <sup>2</sup> control	L1200 x W72 x H76
 <p>113111  <b>Hurdal 1500 White 4820lm 4000K</b>  <b>Ra&gt;80 Sensor Dim</b>  <b>31W LED</b>            155 lm/W SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opal</p>	<b>Class I</b>  <b>IP44</b>  <b>IK07</b>	Sensor Dim	Surface, Indoor 6-pole screwless terminal block with 4x2,5mm <sup>2</sup> through wiring+2x1,5mm <sup>2</sup> control	L1500 x W72 x H76