

Rax Eco 180-190



Rax Eco 180-190 is a super-flexible and cost-effective downlight for general lighting in public buildings, offices, corridors, etc. It has integrated switches for 3000K/4000K and for two lumen levels, i.e. four combinations in one product. A matte white reflector provides high efficiency and low glare with UGR

Rax Eco 180-190




Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212588 Rax Eco 180-190 White 3000/4000K Ra>80 DALI-2 LED 113/124/110/121lm/W SDCM:3 L80/B20>50,000 Beam: 95°, Direct, Reflector	Class II IP20	DALI-2	Indoor 5 pol Linect / screwless terminal block	Ø210 x H93
 212584 Rax Eco 180-190 White 3000/4000K Ra>80 Trailing edge LED 111/116/109/115lm/W SDCM:3 L80/B20>50,000 Beam: 95°, Direct, Reflector	Class II IP20	Trailing edge	Indoor 3 pol Linect / screwless terminal block	Ø210 x H93
Accessories				
 212913 Rax Eco 180-190 Black Glass clear IP44				Ø214 x H12
 212915 Rax Eco 180-190 Black Glass frosted IP44				Ø214 x H12
 212912 Rax Eco 180-190 White Glass clear IP44				Ø214 x H12
 212914 Rax Eco 180-190 White Glass frosted IP44				Ø214 x H12
 820489 Sensor Dim Box White 200VA				L220 x W75 x H34
 8249038725 Rax 200 Mounting plate				L585 x W260 x H15