

Sense Line



Create your own design in T-profile ceilings with Sense Line 600. Sense Line is also available in 1200mm length. The luminaire has a light steel housing and a 3-layer optical system for low glare with UGR

Sense Line



Product- and environment images





Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212691 Sense Line 120x600 White Linect 1160lm 3000K Ra>80 DALI-2 10W LED 116 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W118 x H35
 212695 Sense Line 120x1200 White Linect 2310lm 3000K Ra>80 DALI-2 19W LED 122 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L1195 x W118 x H35
 212690 Sense Line 120x600 White Linect 1160lm 3000K Ra>80 Trailing edge 9W LED 129 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	L595 x W118 x H35
 212694 Sense Line 120x1200 White Linect 2310lm 3000K Ra>80 Trailing edge 18W LED 128 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	L1195 x W118 x H35
 212693 Sense Line 120x600 White Linect 1230lm 4000K Ra>80 DALI-2 10W LED 123 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W118 x H35
 212697 Sense Line 120x1200 White Linect 2460lm 4000K Ra>80 DALI-2 19W LED 129 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L1195 x W118 x H35

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212692 Sense Line 120x600 White Linect 1230lm 4000K Ra>80 Trailing edge 9W LED 137 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	L595 x W118 x H35
 212696 Sense Line 120x1200 White Linect 2460lm 4000K Ra>80 Trailing edge 18W LED 137 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Direct, Opalprism	Class II SELV IP20	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	L1195 x W118 x H35
Accessories				
 820489 Sensor Dim Box White 200VA				L220 x W75 x H34
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3H				L270 x W75 x H35
 212698 Sense Line Retaining springs				L64 x W31 x H21
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35