

# Sense Pro 300x1200



The Sense panel is well designed and only 10 mm high. A narrow frame ensures attractive look and high efficiency. Sense can be mounted to visible T-rail ceilings without accessories and to concealed T-rail ceilings, DAMPA clip-in ceilings, Troldekt acoustic panels and Gypsum, and surface-mounted using accessories. This makes Sense an all-round quality panel that can be used everywhere. Sense is available in several lumen packages, phase-dimming or DALI depending on which driver kit is selected (accessory).

# Sense Pro 300x1200



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212676  <b>Sense Pro 300x1200 White 3000K</b>  <b>Ra&gt;80</b>  <b>LED</b>            SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Beam: 110°, Direct, Opalprism</p>	<b>Class III</b> <b>IP40/IP20</b> <b>IK06</b>		Recessed Quick connector	L1197 x W297 x H11
 <p>212677  <b>Sense Pro 300x1200 White 4000K</b>  <b>Ra&gt;80</b>  <b>LED</b>            SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Beam: 110°, Direct, Opalprism</p>	<b>Class III</b> <b>IP40/IP20</b> <b>IK06</b>		Recessed Quick connector	L1197 x W297 x H11
 <p>212727  <b>Sense Pro 300x1200 White 4000K</b>  <b>Ra&gt;90</b>  <b>LED</b>            SDCM:3            L80/B20&gt;100,000, L90&gt;50,000            Direct, Opalprism</p>	<b>Class III</b> <b>IP40/IP20</b> <b>IK06</b>		Recessed, Indoor Quick connector	L1197 x W297 x H11
<b>Drivers</b>				
 <p>820083  <b>Sense Driver White 3000lm 25W</b>  <b>700mA DALI-2 / Push Dim</b>  <b>25W</b>            100,000</p>	<b>Class II</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L124 x W79 x H22
 <p>820404  <b>Sense Driver White 4000lm 32W</b>  <b>900mA DALI-2 / Push Dim</b>  <b>32W</b>            100,000</p>	<b>Class II</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L138 x W67 x H29
 <p>820490  <b>Sense Driver White 3000lm 25W</b>  <b>700mA Trailing edge</b>  <b>25W</b>            100,000</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Cable 2m Includes cable and plug	L108 x W53 x H30

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>820492  <b>Sense Driver White 4000lm 32W</b>  <b>900mA Trailing edge</b>  <b>32W</b>            100,000</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Cable 2m Includes cable and plug	L108 x W67 x H22
 <p>820491  <b>Sense Driver White 3000lm 25W</b>  <b>700mA Trailing edge / Linect</b>  <b>25W</b>            100,000</p>	<b>Class II</b> <b>IP20</b>	Trailing edge / Linect	Recessed, Indoor 3 pol Linect / screwless terminal block	L108 x W53 x H30
 <p>820493  <b>Sense Driver White 4000lm 32W</b>  <b>900mA Trailing edge / Linect</b>  <b>32W</b>            100,000</p>	<b>Class II</b> <b>IP20</b>	Trailing edge / Linect	Recessed, Indoor 3 pol Linect / screwless terminal block	L108 x W67 x H22
<b>Accessories</b>				
 <p>212259  <b>Sense 300x1200 Black Surface frame</b></p>				L1203 x W303 x H47
 <p>212937  <b>Sense 300x1200 Black Plaster board/Troldtekt Recessed frame</b></p>				L1240 x W340 x H50
 <p>212257  <b>Sense 300x1200 White Surface frame</b></p>				L1203 x W303 x H47
 <p>820489  <b>Sensor Dim Box White 200VA</b></p>				L220 x W75 x H34
 <p>8249044502  <b>300x1200 White Plaster board/Troldtekt Recessed frame</b></p>				L325 x W1225 x H55
 <p>8246094429  <b>Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</b></p>				L270 x W75 x H35
 <p>212170  <b>Sense 2m Wire kit</b></p>				L2000

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246094364 <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b>				L270 x W75 x H35
 8246094500 <b>Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</b>				L270 x W75 x H35