Arena Eco Connect





Arena Eco Connect is an energy-efficient and practical LED luminaire for warehouses and industrial environments, featuring an integrated SG Connect sensor for smart and energy-saving lighting control. The sensor switches the light on when motion is detected and off after a defined time period, ensuring significant energy savings. It also includes a built-in daylight sensor that can be activated to maintain the desired light level at all times. Arena Eco Connect is available with two sensor variants: Low-Bay for mounting heights up to 5 meters and Mid-Bay for heights up to 12 meters, ensuring optimal detection regardless of installation height. Configuration is simple via the SG Connect Commissioning App, and the luminaire can be used as a standalone unit or as part of a larger system that can easily be expanded or reconfigured as needed. Arena Eco Connect combines high performance with easy installation. It features a hinged component box for quick mounting and can be installed directly on the ceiling with screws or using mounting hooks for horizontal wires. Pre-installed through-wiring and cable entry at both ends make installation even more efficient.

Arena Eco Connect




Product- and environment images





Arena Eco Connect





For line drawing dimensions please see each single article codes on next page

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	607026	Class I	Connect	Surface, Indoor	L1552 x W134 x H72
	Arena Eco Connect Low-Bay 1500	IP20		5-pole screwless terminal block with	
	Grey Wide 10960lm 4000K Ra>80			5x2,5mm ² through wiring	
	Connect				
	76W LED				
	144 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 90°, Direct, Lens				