

Callisto Wall Square



Callisto Wall Square is a compact LED luminaire for walls and ceiling for both outdoor and indoor use. Integrated LED chip, dimmable via phase-dimming. Callisto Wall Square is easy to install, directly 230V with screwless terminal block, three inputs/outputs for cables, with options for hidden and surface mounted cable.

Callisto Wall Square



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	923123 Callisto Wall Square Black 130lm 2700K Ra>80 Trailing edge 3W LED 43 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor	L110 x W110 x H33
	923126 Callisto Wall Square Graphite 130lm 2700K Ra>80 Trailing edge 3W LED 43 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor	L110 x W110 x H33
	923120 Callisto Wall Square White 130lm 2700K Ra>80 Trailing edge 3W LED 43 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor	L110 x W110 x H33
	923124 Callisto Wall Square Black 140lm 3000K Ra>80 Trailing edge 3W LED 47 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor	L110 x W110 x H33
	923127 Callisto Wall Square Graphite 140lm 3000K Ra>80 Trailing edge 3W LED 47 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor	L110 x W110 x H33
	923121 Callisto Wall Square White 140lm 3000K Ra>80 Trailing edge 3W LED 47 lm/W SDCM:3	Class II IP65 IK06	Trailing edge	Surface, Indoor / Outdoor	L110 x W110 x H33

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear 923125	Class II	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L110 x W110 x H33
	Callisto Wall Square Black 140lm 4000K Ra>80 Trailing edge 3W LED 47 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	IP65 IK06			
	923128	Class II	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L110 x W110 x H33
	Callisto Wall Square Graphite 140lm 4000K Ra>80 Trailing edge 3W LED 47 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	IP65 IK06			
	923122	Class II	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L110 x W110 x H33
	Callisto Wall Square White 140lm 4000K Ra>80 Trailing edge 3W LED 47 lm/W SDCM:3 L70/B50>50,000 Beam: 80°/45°, Direct/Asymmetric, Glass Clear	IP65 IK06			
Accessories					
	790				L106 x W106 x H18
	Callisto Black Reflector				