

Herning Bollard & Pole



With its combination of modern elegance and classic design, Herning Bollard is ideal for illuminating driveways, gardens, or other outdoor areas. Its glare-free light creates a pleasant atmosphere while providing optimal illumination. The bollard is compatible with both the Herning Mini and Midi pole heads, allowing you to create a cohesive look in your outdoor space with bollards, poles, and wall lights in the same timeless design. The bollard and pole head are sold separately. Herning Bollard is made from durable, powder-coated aluminum, and the luminaire has a tempered glass front. Behind the glass, you'll find practical switches that let you choose between 3000K or 4000K color temperatures, as well as two different light levels—offering four combinations in a single fixture. It comes preset to 3000K and the highest light level but can easily be adjusted to suit your lighting needs. This phase-cut dimmable bollard can be mounted directly on the ground or cast in with an anchor bracket (sold separately), and a mounting plate compatible with the Ørsta foundation is available as an accessory.

Herning Bollard & Pole










Product- and environment images






Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>623978 Herning Polehead Ø60 Black Mini 580/620/1220/1300lm 3000/4000K Ra>80 Trailing edge LED 73/78/72/76lm/W SDCM:3 L80/B20>50,000 Direct, Glass</p>	Class II IP65 IK06	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Cable 2x1mm ² 3m	L342 x W182 x H144
 <p>623979 Herning Polehead Ø60 Black Midi 1060/1140/1770/1920lm 3000/4000K Ra>80 Trailing edge LED 82/88/71/77lm/W SDCM:3 L80/B20>50,000 Direct, Glass</p>	Class II IP65 IK06	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Cable 2x1mm ² 3m	L400 x W240 x H189
 <p>623980 Herning Polehead Ø60 Grey Mini 580/620/1220/1300lm 3000/4000K Ra>80 Trailing edge LED 73/36/72/76lm/W SDCM:3 L80/B20>50,000 Direct, Glass</p>	Class II IP65 IK06	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Cable 2x1mm ² 3m	L342 x W182 x H144
 <p>623981 Herning Polehead Ø60 Grey Midi 1060/1140/1770/1920lm 3000/4000K Ra>80 Trailing edge LED 82/88/71/77lm/W SDCM:3 L80/B20>50,000 Direct, Glass</p>	Class II IP65 IK06	Trailing edge	Pole, wall, bollard or earthing rod, Outdoor Cable 2x1mm ² 3m	L400 x W240 x H189
Accessories				
 <p>623972 Herning Pole 2,5M Ø60 Black</p>				Ø60 x H2500
 <p>623975 Herning Bollard 900 Ø60 Black</p>				Ø60 x H855
 <p>623973 Herning Pole 2,5M Ø60 Grey</p>				Ø60 x H2500

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 623976 Herning Bollard 900 Ø60 Grey				Ø60 x H855
 623984 Fixingplate for Ørsta Foundation				L200 x W200 x H8
 8249042067 Ground anchor				Ø155 x L248 x W108 x H450