

Inspire Prism



Inspire Prism has a slim, modern design with powder-coated white or black outer surface. Direct light with prismatic, glare-free optics made of PMMA, combined with indirect light with a wide beam angle, gives an efficient light perfectly suited for offices and above desks. 2,5m cable and wireset for ceiling/T-profile fixing is included. Different control options are available; phase cut, pull-dim or DALI. If you want to position several luminaires in a row, the luminaires can easily be connected together with the supplied coupling piece or the flexible corner (accessory).

Inspire Prism



Product- and environment images




Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212493 Inspire 1200 Black prism 3510lm 3000K Ra>80 DALI-2 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	DALI-2	Suspended, Indoor 2x2m wire kit Cable 5x0,75mm² 2,5m	L1240 x W38 x H67
	212863 Inspire 1500 Black prism 4330lm 3000K Ra>80 DALI-2 35W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	DALI-2	Suspended, Indoor 2x2m wire kit Cable 5x0,75mm² 2,5m	L1465 x W38 x H67
	212492 Inspire 1200 Black prism 3510lm 3000K Ra>80 Dim 1x pull switch 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1240 x W38 x H67
	212862 Inspire 1500 Black prism 4330lm 3000K Ra>80 Dim 1x pull switch 35W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1465 x W38 x H67
	212853 Inspire 1200 Black prism 3510lm 3000K Ra>80 PIR Sensor 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	PIR Sensor	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1240 x W38 x H67
	212871 Inspire 1500 Black prism 4060lm 3000K Ra>80 PIR Sensor 34W LED 119 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	PIR Sensor	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1465 x W38 x H67



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212852	Class I	Trailing edge	Suspended, Indoor	L1240 x W38 x H67
	Inspire 1200 Black prism 3510lm 3000K Ra>80 Trailing edge 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm ² 2,5m	
	212870	Class I	Trailing edge	Suspended, Indoor	L1465 x W38 x H67
	Inspire 1500 Black prism 4330lm 3000K Ra>80 Trailing edge 35W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm ² 2,5m	
	212491	Class I	DALI-2	Suspended, Indoor	L1240 x W38 x H67
	Inspire 1200 White prism 4000lm 3000K Ra>80 DALI-2 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 5x0,75mm ² 2,5m	
	212861	Class I	DALI-2	Suspended, Indoor	L1465 x W38 x H67
	Inspire 1500 White prism 4800lm 3000K Ra>80 DALI-2 35W LED 137 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 5x0,75mm ² 2,5m	
	212490	Class I	Dim 1x pull switch	Suspended, Indoor	L1240 x W38 x H67
	Inspire 1200 White prism 4000lm 3000K Ra>80 Dim 1x pull switch 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm ² 2,5m	
	212860	Class I	Dim 1x pull switch	Suspended, Indoor	L1465 x W38 x H67
	Inspire 1500 White prism 4800lm 3000K Ra>80 Dim 1x pull switch 35W LED 137 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm ² 2,5m	

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212851	Class I	PIR Sensor	Suspended, Indoor	L1240 x W38 x H67
	Inspire 1200 White prism 4000lm 3000K Ra>80 PIR Sensor 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm² 2,5m	
	212869	Class I	PIR Sensor	Suspended, Indoor	L1465 x W38 x H67
	Inspire 1500 White prism 4510lm 3000K Ra>80 PIR Sensor 34W LED 133 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm² 2,5m	
	212850	Class I	Trailing edge	Suspended, Indoor	L1240 x W38 x H67
	Inspire 1200 White prism 4000lm 3000K Ra>80 Trailing edge 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm² 2,5m	
	212868	Class I	Trailing edge	Suspended, Indoor	L1465 x W38 x H67
	Inspire 1500 White prism 4800lm 3000K Ra>80 Trailing edge 35W LED 137 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 3x0,75mm² 2,5m	
	212497	Class I	DALI-2	Suspended, Indoor	L1240 x W38 x H67
	Inspire 1200 Black prism 3620lm 4000K Ra>80 DALI-2 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 5x0,75mm² 2,5m	
	212867	Class I	DALI-2	Suspended, Indoor	L1465 x W38 x H67
	Inspire 1500 Black prism 4470lm 4000K Ra>80 DALI-2 35W LED 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	IP20		2x2m wire kit Cable 5x0,75mm² 2,5m	


Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212496 Inspire 1200 Black prism 3620lm 4000K Ra>80 Dim 1x pull switch 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1240 x W38 x H67
	212866 Inspire 1500 Black prism 4470lm 4000K Ra>80 Dim 1x pull switch 35W LED 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1465 x W38 x H67
	212857 Inspire 1200 Black prism 3620lm 4000K Ra>80 PIR Sensor 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	PIR Sensor	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1240 x W38 x H67
	212875 Inspire 1500 Black prism 4200lm 4000K Ra>80 PIR Sensor 34W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	PIR Sensor	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1465 x W38 x H67
	212856 Inspire 1200 Black prism 3620lm 4000K Ra>80 Trailing edge 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Trailing edge	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1240 x W38 x H67
	212874 Inspire 1500 Black prism 4470lm 4000K Ra>80 Trailing edge 35W LED 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Trailing edge	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1465 x W38 x H67

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212495 Inspire 1200 White prism 4130lm 4000K Ra>80 DALI-2 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	DALI-2	Suspended, Indoor 2x2m wire kit Cable 5x0,75mm ² 2,5m	L1240 x W38 x H67
	212865 Inspire 1500 White prism 4960lm 4000K Ra>80 DALI-2 35W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	DALI-2	Suspended, Indoor 2x2m wire kit Cable 5x0,75mm ² 2,5m	L1465 x W38 x H67
	212494 Inspire 1200 White prism 4130lm 4000K Ra>80 Dim 1x pull switch 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm ² 2,5m	L1240 x W38 x H67
	212864 Inspire 1500 White prism 4960lm 4000K Ra>80 Dim 1x pull switch 35W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm ² 2,5m	L1465 x W38 x H67
	212855 Inspire 1200 White prism 4130lm 4000K Ra>80 PIR Sensor 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	PIR Sensor	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm ² 2,5m	L1240 x W38 x H67
	212873 Inspire 1500 White prism 4660lm 4000K Ra>80 PIR Sensor 34W LED 137 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	PIR Sensor	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm ² 2,5m	L1465 x W38 x H67

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212854 Inspire 1200 White prism 4130lm 4000K Ra>80 Trailing edge 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Trailing edge	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1240 x W38 x H67
 212872 Inspire 1500 White prism 4960lm 4000K Ra>80 Trailing edge 35W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	Class I IP20	Trailing edge	Suspended, Indoor 2x2m wire kit Cable 3x0,75mm² 2,5m	L1465 x W38 x H67
Accessories				
 212198 Black T-carrier ceiling bracket				L30 x W20 x H5
 212470 Inspire Black Corner piece flex				L78 x W38 x H67
 212255 T-profil White Suspension Rail 600mm				L596 x W35 x H17
 212471 Inspire White Corner piece flex				L78 x W38 x H67