

Tysnes 66 Connect Wireless



Tysnes Connect Wireless is a sealed, slim LED luminaire designed for storage rooms, garages, and parking facilities, featuring an integrated Connect Wireless driver for smart, energy-efficient lighting control. The luminaire is used in combination with other SG Connect devices such as sensors or Connect Switch. Lighting control is easily configured via the SG Connect Commissioning App, and devices communicate wirelessly over Zigbee for flexible, scalable control. Tysnes Connect Wireless offers low power consumption, high light output, and long service life. It can be mounted directly on the ceiling using robust steel clips or with wire suspension. Cable entry at both ends and a knockout for rear cabling simplify installation. The series is available in two lengths to suit different needs.

Tysnes 66 Connect Wireless



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>120055 Tysnes 66 Connect 1200 Grey 5530lm 4000K Ra>80 Connect Wireless 32W LED 173 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 121°, Direct, Opal</p>	<p>Class II IP66 IK10</p>	<p>Connect Wireless</p>	<p>Surface, Indoor 3-pole screwless terminal block with 3x2,5mm² through wiring</p>	<p>L1200 x W85 x H80</p>
 <p>120056 Tysnes 66 Connect 1500 Grey 5560lm 4000K Ra>80 Connect Wireless 32W LED 174 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 121°, Direct, Opal</p>	<p>Class II IP66 IK10</p>	<p>Connect Wireless</p>	<p>Surface, Indoor 3-pole screwless terminal block with 3x2,5mm² through wiring</p>	<p>L1500 x W85 x H80</p>
Accessories				
 <p>8249044900 Wirekit 2x5m</p>				<p>L19 x W25 x H150</p>
 <p>8249044913 Mounting kit for adjustable angulation</p>				<p>L100 x W98 x H95</p>