

Rax Soft 150 Connect Wireless










A version of Rax Soft 150, which is combined with a wide range of SG Connect Driver Kit Wireless to provide the desired amount of light. The lighting control is easy to configure using the SG Connect Commissioning App, and the luminaire can be used with a wireless sensor or as part of a larger system, along with other SG Connect luminaires with integrated sensors, which can easily be enlarged or reconfigured as needed. The light is turned on and off after a defined period of time, contributing to energy saving. Rax Soft Connect is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm.

Rax Soft 150 Connect Wireless










Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212770 Rax Soft 150 Satin 3000K Ra>80 Connect Wireless LED SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	Class II SELV IP44/IP20 IK07	Connect Wireless	Recessed, Indoor Quick connector	Ø166 x H83
 <p>212771 Rax Soft 150 Satin 4000K Ra>80 Connect Wireless LED SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	Class II SELV IP44/IP20 IK07	Connect Wireless	Recessed, Indoor Quick connector	Ø166 x H83
Drivers				
 <p>820503 Driver kit Wireless 13W 300mA Connect 13W 100,000</p>	Class II IP20	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L157 x W45 x H30
 <p>820504 Driver kit Wireless 18W 500mA Connect 18W 100,000</p>	Class II IP20	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L157 x W45 x H30
 <p>820506 Driver kit Wireless 26W 700mA Connect 26W 100,000</p>	Class II IP20	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L157 x W45 x H30
Accessories				
 <p>212617 Rax 150 Black Rehabring Ø155-200mm</p>				Ø220 x H16
 <p>212621 Rax 150 Black Glass clear IP44</p>				Ø168 x H12

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212623 Rax 150 Black Glass frosted IP44				Ø168 x H12
 212620 Rax 150 White Glass clear IP44				Ø168 x H12
 212622 Rax 150 White Glass frosted IP44				Ø168 x H12
 8249044683 Rax 150 White Rehabring Ø155-200mm				Ø220 x H16
 900109 Reliefplate				L400 x W400 x H1
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8249042216 Rax 150 Mounting plate				L585 x W260 x H15