

# Sense Pro Connect 300x1200



Sense Pro Connect is an energy-efficient LED panel with a slim frame for a clean, modern look. It features an integrated SG Connect sensor for smart, energy-efficient lighting control. The sensor switches the light on when motion is detected and off after a defined time period, delivering significant energy savings. A built-in daylight sensor can be activated to maintain the desired light level at all times. Configuration is simple via the SG Connect Commissioning App, and the panel can be used as a standalone unit or as part of a larger system that can easily be expanded or reconfigured as needed. Sense Pro Connect is a high-quality, all-round panel suitable for all kinds of environments. It can be installed in ceilings with exposed T-grids without accessories, and in ceilings with concealed T-grids using appropriate accessories.

# Sense Pro Connect 300x1200



## Product- and environment images



# Sense Pro Connect 300x1200



For line drawing dimensions please see each single article codes on next page

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212686  <b>Sense Pro Connect 300x1200 White</b>  <b>3000K Ra&gt;80 Connect</b>  <b>LED</b>                      SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 110°, Direct, Opalprism</p>	<b>Class III</b> <b>IP40/IP20</b>	Connect	Recessed, Indoor Quick connector	L1197 x W297 x H11
 <p>212687  <b>Sense Pro Connect 300x1200 White</b>  <b>4000K Ra&gt;80 Connect</b>  <b>LED</b>                      SDCM:3                      L80/B20&gt;100,000, L90&gt;50,000                      Beam: 110°, Direct, Opalprism</p>	<b>Class III</b> <b>IP40/IP20</b>	Connect	Recessed, Indoor Quick connector	L1197 x W297 x H11
<b>Drivers</b>				
 <p>820511  <b>Driver kit Sensor 25W 700mA</b>  <b>Connect</b>  <b>25W</b>                      100,000</p>	<b>Class II</b> <b>IP20</b>	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L201 x W75 x H33
 <p>820512  <b>Driver kit Sensor 32W 900mA</b>  <b>Connect</b>  <b>32W</b>                      100,000</p>	<b>Class II</b> <b>IP20</b>	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L201 x W75 x H33
<b>Accessories</b>				
 <p>212170  <b>Sense 2m Wire kit</b></p>				L2000
 <p>212177  <b>Sense 600x600 Asymmetric Bracket</b></p>				L44 x W5 x H2.5
 <p>8246094364  <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b></p>				L270 x W75 x H35