

Lineal Surface Connect



Version of Lineal Surface which comes complete with driver and integrated wireless SG Connect sensor. The sensor is discreetly positioned at the edge, switches on when it detects movement and switches off after a pre-selected period of time to save energy. The sensor also includes an integrated daylight sensor. If this function is activated, the sensor will constantly work to provide the desired amount of light in its work area. The lighting control is easy to configure using the SG Connect Commissioning App, and the luminaire can be used individually or as part of a larger system, which can easily be enlarged or reconfigured as needed.

Lineal Surface Connect



Product- and environment images





Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>9341000675 Lineal surface 1400 White 2320lm 3000K Ra>80 Connect 21W LED 110 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,</p>	Class I IP20	Connect	Surface, Indoor	L1472 x W42 x H70
 <p>9341000818 Lineal surface 1120 White 1870lm 3000K Ra>80 Connect 17W LED 110 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,</p>	Class I IP20	Connect	Surface, Indoor	L1192 x W42 x H70
 <p>9341000882 Lineal surface 840 White 1380lm 3000K Ra>80 Connect 13W LED 106 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,</p>	Class I IP20	Connect	Surface, Indoor	L912 x W42 x H70
Accessories				
 <p>8241000347 Lineal Wall Extension kit White</p>				L115 x W93 x H64
 <p>8241000355 Lineal T-ceiling Extension kit White</p>				L120 x W94 x H65
 <p>8249045116 Lineal Wire kit 1 x 2m</p>				