

# Tysnes 66 Pro



Tysnes 66 Pro is a very efficient, robust version in the Tysnes 66 family. With very high light output and long lifetime it is the project winner for storage rooms, garages, and parking facilities. The luminaire is produced from impact-resistant UV stabilized polycarbonate, and the components can withstand vibrations and very low temperatures (-40°C). It can easily be mounted on ceilings with clips or suspended in wires. Sturdy steel clips attached to the luminaire holds the diffuser. It has cable entries in both ends and weakening for cabling from the back. 5-pole (On/Off) or 7-pole (DALI) terminal block with 5 x 2,5 mm<sup>2</sup> through wiring gives flexibility for larger installations.

## Product- and environment images



# Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	120053 <b>Tysnes 66 Pro 1500 Grey 9430lm</b> <b>4000K Ra&gt;80 DALI-2</b> <b>55W LED</b> 171 lm/W SDCM:3 L90/B10>100,000, L90>50,000 Beam: 119°, Direct, Opal	<b>Class I</b> <b>IP66</b> <b>IK10</b>	DALI-2	Surface, Indoor Screwless terminal block	L1500 x W85 x H80
	120051 <b>Tysnes 66 Pro 1500 Grey 9430lm</b> <b>4000K Ra&gt;80 On/Off</b> <b>55W LED</b> 171 lm/W SDCM:3 L90/B10>100,000, L90>50,000 Beam: 119°, Direct, Opal	<b>Class I</b> <b>IP66</b> <b>IK10</b>	On/Off	Surface, Indoor Screwless terminal block	L1500 x W85 x H80
	120062 <b>Tysnes 66 Pro 1500 Grey 11060lm</b> <b>6500K Ra&gt;80 On/Off</b> <b>69W LED</b> 160 lm/W SDCM:3 L90/B10>100,000, L90>50,000 Beam: 114°, Direct, Opal	<b>Class I</b> <b>IP66</b> <b>IK10</b>	On/Off	Surface, Indoor 5-pole screwless terminal block with 5x2,5mm <sup>2</sup> through wiring	L1500 x W85 x H80
<b>Accessories</b>					
	120063 <b>Tysnes 66 45° Fastening</b>				L45 x W43 x H43
	8249044900 <b>Wirekit 2x5m</b>				L19 x W25 x H150
	8249044913 <b>Mounting kit for adjustable angulation</b>				L100 x W98 x H95