



Fenes Maxi is a minimalist LED luminaire that combines modern design with the latest in LED technology to deliver optimal performance and energy efficiency. It is an excellent choice for replacing old 125W HQL and 70W NAV fixtures, making it easy to upgrade to LED technology without the need to replace existing poles – a smart and cost-effective solution for outdoor areas such as parks, access roads, large parking lots, and other public spaces. The luminaire is designed for flexibility, featuring a multi-adapter that fits both poles Ø60mm and side arm Ø42/48mm, and can be adjusted in steps of 5°, ensuring the perfect light angle every time. Choose from various dimming and control techniques to tailor the lighting to different needs. Fenes Maxi is made of powder-coated, die-cast aluminum and tempered glass. It is delivered complete with an 8 meter cable for easy installation and is built to withstand ambient temperatures as low as -40°C

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212776 Fenes Maxi Lens 2 Grey 6350lm 3000K Ra>70 DALI-2 43W LED 148 lm/W SDCM:3 L80/B20>100,000 Direct, PMMA, Polymethylmethacrylat	Class II IP66 IK08	DALI-2	Pole - Side Top (Ø42-48/Ø60), Outdoor Cable 4x1.0mm ² 8m, H05RN-F	L432 x W188 x H145
	212777 • Fenes Maxi Lens 2 Grey 6350lm 3000K Ra>70 DYNADIM 43W LED 148 lm/W SDCM:3 L80/B20>100,000 Direct, PMMA, Polymethylmethacrylat	Class II IP66 IK08	DYNADIM	Pole - Side Top (Ø42-48/Ø60), Outdoor Cable 2x1.0mm ² 8m, H05RN-F	L432 x W188 x H145
	212775 Fenes Maxi Lens 2 Grey 6350lm 3000K Ra>70 On/Off 43W LED 148 lm/W SDCM:3 L80/B20>100,000 Direct, PMMA, Polymethylmethacrylat	Class II IP66 IK08	On/Off	Pole - Side Top (Ø42-48/Ø60), Outdoor Cable 2x1.0mm ² 8m, H05RN-F	L432 x W188 x H145
	212790 Fenes Maxi Lens 2 Grey 6830lm 4000K Ra>70 DALI-2 43W LED 159 lm/W SDCM:3 L80/B20>100,000 Direct, PMMA, Polymethylmethacrylat	Class II IP66 IK08	DALI-2	Pole - Side Top (Ø42-48/Ø60), Outdoor Cable 4x1.0mm ² 8m, H05RN-F	L432 x W188 x H145
	212789 Fenes Maxi Lens 2 Grey 6830lm 4000K Ra>70 On/Off 43W LED 159 lm/W SDCM:3 L80/B20>100,000 Direct, PMMA, Polymethylmethacrylat	Class II IP66 IK08	On/Off	Pole - Side Top (Ø42-48/Ø60), Outdoor Cable 2x1.0mm ² 8m, H05RN-F	L432 x W188 x H145

Accessories

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
	623268			Ø60 x L130 x W127 x H154
	623269			Ø60 x L130 x W110 x H92

• = This article is produced by order, with an expected delivery time of 3-4 weeks.