

Hurdal Connect



Hurdal Connect is a compact and stylish ceiling and wall luminaire featuring an integrated SG Connect sensor for smart and energy-efficient lighting control. The sensor switches the light on when motion is detected and off after a defined time period, delivering significant energy savings. A built-in daylight sensor can be activated to maintain the desired light level at all times. Configuration is simple via the SG Connect Commissioning App, and the luminaire can be used as a standalone unit or as part of a larger system that can easily be expanded or reconfigured as needed. Hurdal Connect combines high performance with easy installation. It mounts directly on ceilings or walls, with cable entry at both ends and in the middle, and through-wiring ensures quick and efficient connection. The luminaire is IP44-rated and features a robust steel housing with aluminum end caps for long-lasting and reliable operation.

Hurdal Connect



Product- and environment images





Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>113126 Hurdal Connect 600 White 1590lm 3000K Ra>80 Connect 12W LED 133 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opal</p>	Class I IP44	Connect	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L600 x W72 x H76
 <p>113127 Hurdal Connect 1200 White 3460lm 3000K Ra>80 Connect 24W LED 144 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opal</p>	Class I IP44	Connect	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1200 x W72 x H76
 <p>113128 Hurdal Connect 1500 White 4640lm 3000K Ra>80 Connect 31W LED 150 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opal</p>	Class I IP44	Connect	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1500 x W72 x H76
 <p>113158 Hurdal 600 White 1710lm 4000K Ra>80 Connect 12W LED 143 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opal</p>	Class I IP44	Connect	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L600 x W72 x H76
 <p>113159 Hurdal 1200 White 3660lm 4000K Ra>80 Connect 24W LED 153 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opal</p>	Class I IP44	Connect	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1200 x W72 x H76
 <p>113160 Hurdal 1500 White 4820lm 4000K Ra>80 Connect 31W LED 155 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opal</p>	Class I IP44	Connect	Surface, Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1500 x W72 x H76