



Luminaire for general lighting for the ShopLine three-phase track system. Can also be used with other track systems that utilize Global. Stylish, slim fixture with lens technology that directs the light where it's needed. The driver is integrated into the track adapter and includes dip switches, facilitating adjustment of light output or reduced UGR.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	607044	Class II SELV	On/Off	Surface, Indoor ShopLine track (adapter included)	L583 x W69 x H69
Arena 600 3-Circuit Black Medium		IP20			
3420lm 3000K Ra>90 On/Off					
26W LED					
132 lm/W SDCM:3					
L90/B10>100,000					
Beam: 60°, Direct,					
	607040	Class II SELV	On/Off	Surface, Indoor ShopLine track (adapter included)	L583 x W69 x H69
Arena 600 3-Circuit White Medium		IP20			
3690lm 3000K Ra>90 On/Off					
26W LED					
142 lm/W SDCM:3					
L90/B10>100,000					
Beam: 60°, Direct,					
	607046	Class II SELV	On/Off	Surface, Indoor ShopLine track (adapter included)	L583 x W69 x H69
Arena 600 3-Circuit Black Medium		IP20			
3800lm 4000K Ra>90 On/Off					
26W LED					
146 lm/W SDCM:3					
L90/B10>100,000					
Beam: 60°, Direct,					
	607042	Class II SELV	On/Off	Surface, Indoor ShopLine track (adapter included)	L583 x W69 x H69
Arena 600 3-Circuit White Medium		IP20			
4100lm 4000K Ra>90 On/Off					
26W LED					
158 lm/W SDCM:3					
L90/B10>100,000					
Beam: 60°, Direct,					