

Ecoline D/I



EcoLine D/I is a slim and stylish suspended luminaire that is designed for quick and easy installation.
Direct light with three layer optical system for glare-free light (UGR

Ecoline D/I



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212804	Class I	DALI-2	Suspended, Indoor	L1235 x W166 x H58
	EcoLine 1200 White D/I 4650lm 3000K Ra>80 DALI-2 32W LED 145 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		2x2m wire kit Cable 5x0,75mm ² 2,5m	
	212806	Class I	DALI-2	Suspended, Indoor	L1600 x W166 x H58
	EcoLine 1600 White D/I 5430lm 3000K Ra>80 DALI-2 35W LED 155 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		2x2m wire kit Cable 5x0,75mm ² 2,5m	
	212812	Class I	On/Off	Suspended, Indoor	L1235 x W166 x H58
	EcoLine 1200 White D/I 4650lm 3000K Ra>80 On/Off 32W LED 145 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		2x2m wire kit Cable 3x0,75mm ² 2,5m	
	212814	Class I	On/Off	Suspended, Indoor	L1600 x W166 x H58
	EcoLine 1600 White D/I 5430lm 3000K Ra>80 On/Off 35W LED 155 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		2x2m wire kit Cable 3x0,75mm ² 2,5m	
	212805	Class I	DALI-2	Suspended, Indoor	L1235 x W166 x H58
	EcoLine 1200 White D/I 4850lm 4000K Ra>80 DALI-2 32W LED 152 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		2x2m wire kit Cable 5x0,75mm ² 2,5m	
	212807	Class I	DALI-2	Suspended, Indoor	L1600 x W166 x H58
	EcoLine 1600 White D/I 5640lm 4000K Ra>80 DALI-2 35W LED 161 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprism	IP20		2x2m wire kit Cable 5x0,75mm ² 2,5m	

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212813	Class I	On/Off	Suspended, Indoor	L1235 x W166 x H58
	EcoLine 1200 White D/I 4850lm	IP20		2x2m wire kit	
	4000K Ra>80 On/Off			Cable 3x0,75mm ² 2,5m	
	32W LED				
	152 lm/W SDCM:3				
 <i>Not released yet</i>	212815	Class I	On/Off	Suspended, Indoor	L1600 x W166 x H58
	EcoLine 1600 White D/I 5640lm	IP20		2x2m wire kit	
	4000K Ra>80 On/Off			Cable 3x0,75mm ² 2,5m	
	35W LED				
	161 lm/W SDCM:3				
	L90/B10>100,000, L96>50,000				
	Direct/Indirect, Opalprism				