



The Sense Basic LED panel is the perfect choice for price sensitive projects, both for new installations and remodelling. It has a lightweight steel housing only 36 mm high and it is based on backlight. Now available in a single pack, complete with driver. Various dimming options are available with phase-cut or DALI.

Sense Basic 2



Product- and environment images





Article codes




Article	Protection	Control gear	Mounting/Connection	Dimensions
 212795 Sense Basic 625x625 White Incl driver 4340lm 3000K Ra>80 DALI-2 33W LED 132 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism	Class II SELV IP20 IK06	DALI-2	Recessed, Indoor Screwless terminal block	L620 x W620 x H29
 212214 Sense Basic 600x600 White Incl driver 4320lm 3000K Ra>80 DALI-2 LINECT 33W LED 131 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism	Class II SELV IP20 IK06	DALI-2 LINECT	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W595 x H36
 212218 Sense Basic 600x600 White Cable and plug 2m 3070lm 3000K Ra>80 Trailing edge 23W LED 133 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism	Class II SELV IP20 IK06	Trailing edge	Recessed, Indoor Cable 2m Includes cable and plug	L595 x W595 x H36
 212213 Sense Basic 600x600 White Incl driver 4320lm 3000K Ra>80 Trailing edge / Linect 33W LED 131 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism	Class II SELV IP20 IK06	Trailing edge / Linect	Recessed, Indoor 3 pol Linect / screwless terminal block	L595 x W595 x H36
 212794 Sense Basic 625x625 White Incl driver 4340lm 3000K Ra>80 Trailing edge / Linect 33W LED 132 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism	Class II SELV IP20 IK06	Trailing edge / Linect	Recessed, Indoor 3 pol Linect / screwless terminal block	L620 x W620 x H29
 212216 Sense Basic 600x600 White Incl driver 4390lm 4000K Ra>80 DALI-2 LINECT 33W LED 133 lm/W SDCM:3	Class II SELV IP20 IK06	DALI-2 LINECT	Recessed, Indoor 5 pol Linect / screwless terminal block	L595 x W595 x H36

Article codes



Article	L80/B20>100,000	Protection	Control gear	Mounting/Connection	Dimensions
	212215	Class II SELV	Trailing edge /	Recessed, Indoor	L595 x W595 x H36
	Sense Basic 600x600 White Incl driver 4390lm 4000K Ra>80 Trailing edge / Linect 33W LED	IP20	Linect	3 pol Linect / screwless terminal block	
	133 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism				
	212796	Class II SELV	Trailing edge /	Recessed, Indoor	L620 x W620 x H29
	Sense Basic 625x625 White Incl driver 4310lm 4000K Ra>80 Trailing edge / Linect 33W LED	IP20	Linect	3 pol Linect / screwless terminal block	
	131 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism				
Accessories					
	212688				L597 x W597 x H79
	Sense Decor Sky White 600x600				
	212689				L622 x W622 x H79
	Sense Decor Sky 625x625 White				
	212780				L595 x W595 x H17
	Sense Decor Soft White 600x600				
	820489				L220 x W75 x H34
	Sensor Dim Box White 200VA				
	8249045006				L640 x W640 x H40
	Sense 600x600 White Plaster board/Troldtekt Recessed frame				
	212792				L643 x W627 x H85
	Sense Basic 625x625				
	8246094364				L270 x W75 x H35
	Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35