

Disc 480 D/I



Disc 480 D/I is an energy efficient and stylish surface-mounted luminaire with a slim profile, providing any room with a modern and refined look. Opal prismatic diffuser ensures glare-free and comfortable lighting with a decorative indirect light. It is possible to choose between 3000K/4000K with the connection cable. Disc 480 D/I is produced in durable aluminium and polycarbonate. Installation is simple, thanks to the quick connection between the luminaire and the backplate, which can be mounted directly onto all standard ceiling boxes. Visible cabling also possible.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	606201 Disc 480 Black D/I 3940lm 2700K Ra>80 Trailing edge 34W LED 116 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø467 x H62
	606200 Disc 480 White D/I 4220lm 2700K Ra>80 Trailing edge 34W LED 124 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø467 x H62
	606205 Disc 480 Black D/I 4000/4270lm 3000/4000K Ra>80 DALI-2 / Push Dim 34W LED 118 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø467 x H62
	606209 Disc 480 Black D/I 4000/4270lm 3000/4000K Ra>80 Sensor Dim 34W LED 118 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Sensor Dim	Surface, Indoor Screwless terminal block	Ø467 x H62
	606182 Disc 480 Black D/I 4000/4270lm 3000/4000K Ra>80 Trailing edge 34W LED 118/126 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø467 x H62
	606204 Disc 480 White D/I 4160/4420lm 3000/4000K Ra>80 DALI-2 / Push Dim 34W LED 122 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	Ø467 x H62

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	606208	Class II	Sensor Dim	Surface, Indoor	Ø467 x H62
	Disc 480 White D/I 4160/4420lm	IP20		Screwless terminal block	
	3000/4000K Ra>80 Sensor Dim	IK10			
	34W LED				
	122 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism				
	606180	Class II	Trailing edge	Surface, Indoor	Ø467 x H62
	Disc 480 White D/I 4160/4420lm	IP20		Screwless terminal block	
	3000/4000K Ra>80 Trailing edge	IK10			
	34W LED				
	122/130 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism				
Accessories					
	606095				L5000 x W102 x H22
	Disc/Frosta Black Pendant Adapter				
	606094				L5000 x W102 x H22
	Disc/Frosta White Pendant Adapter				