

Disc 290 D/I



Disc 290 D/I is an energy efficient and stylish surface-mounted luminaire with a slim profile, providing any room with a modern and refined look. Opal prismatic diffuser ensures glare-free and comfortable lighting with a decorative indirect light. It is possible to choose between 3000K/4000K with the connection cable. Disc 290 D/I is produced in durable aluminium and polycarbonate. Installation is simple, thanks to the quick connection between the luminaire and the backplate, which can be mounted directly onto all standard ceiling boxes. Visible cabling also possible.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	606203 Disc 290 Black D/I 1860lm 2700K Ra>80 Trailing edge 18W LED 103 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø290 x H62
	606202 Disc 290 White D/I 1940lm 2700K Ra>80 Trailing edge 18W LED 108 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø290 x H62
	606207 Disc 290 Black D/I 1840/1970lm 3000/4000K Ra>80 DALI-2 18W LED 102 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	DALI-2	Surface, Indoor Screwless terminal block	Ø290 x H62
	606211 Disc 290 Black D/I 1840/1970lm 3000/4000K Ra>80 Sensor Dim 18W LED 102 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Sensor Dim	Surface, Indoor Screwless terminal block	Ø290 x H62
	606185 Disc 290 Black D/I 1840/1970lm 3000/4000K Ra>80 Trailing edge 18W LED 102/109 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø290 x H62
	606206 Disc 290 White D/I 2000/2140lm 3000/4000K Ra>80 DALI-2 18W LED 111 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	DALI-2	Surface, Indoor Screwless terminal block	Ø290 x H62

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	606210 Disc 290 White D/I 2000/2140lm 3000/4000K Ra>80 Sensor Dim 18W LED 111 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Sensor Dim	Surface, Indoor Screwless terminal block	Ø290 x H62
	606184 Disc 290 White D/I 2000/2140lm 3000/4000K Ra>80 Trailing edge 18W LED 111/119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø290 x H62
Accessories					
	606095 Disc/Frosta Black Pendant Adapter				L5000 x W102 x H22
	606094 Disc/Frosta White Pendant Adapter				L5000 x W102 x H22