

Sense Basic Surface



Sense Basic Surface is the perfect choice for price-sensitive projects, both for new installations or remodeling. The luminaire features a steel housing with clean, straight lines – a lightweight construction that makes it easy to install without tools. The front is held in place by strong magnets, and there is a quick connection between the bracket and the front. An innovative mechanism allows you to choose whether the front should be flush with the ceiling for hidden cabling or floating slightly below for surface cabling. You can easily select between 3000K or 4000K in each luminaire, and in phase-cut dimming variants, the light level can be adjusted up or down to the desired level via dip switches.

Sense Basic Surface



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212701	Class II SELV	DALI-2	Indoor 5 pol Screwless terminal block	L600 x W600 x H66
	Sense Basic Surface 600x600 White	IP20			
	4370/4390lm 3000/4000K Ra>80	IK06			
	DALI-2				
	31W LED				
	141 lm/W SDCM:3				
	L80/B20>100,000				
	Direct, Opalprism				
	212704	Class II SELV	DALI-2	Indoor 5 pol Screwless terminal block	L1202 x W301 x H66
	Sense Basic Surface 300x1200	IP20			
	White 4290/4510lm 3000/4000K	IK06			
	Ra>80 DALI-2				
	32W LED				
	134 lm/W SDCM:3				
	L80/B20>100,000				
	Direct, Opalprism				
	212700	Class II SELV	Trailing edge	Indoor 3 pole Screwless terminal block	L600 x W600 x H66
	Sense Basic Surface 600x600 White	IP20			
	4370/4390lm 3000/4000K Ra>80	IK06			
	Trailing edge				
	31W LED				
	141 lm/W SDCM:3				
	L80/B20>100,000				
	Direct, Opalprism				
	212703	Class II SELV	Trailing edge	Indoor 3 pole Screwless terminal block	L1202 x W301 x H66
	Sense Basic Surface 300x1200	IP20			
	White 4290/4510lm 3000/4000K	IK06			
	Ra>80 Trailing edge				
	32W LED				
	134 lm/W SDCM:3				
	L80/B20>100,000				
	Direct, Opalprism				