



Hurdal Maxi is a versatile surface-mounted luminaire that combines high performance with easy installation. The wide range of variants covers most needs, from general lighting to more advanced control solutions. Perfect for projects where quality, efficiency, and flexibility are essential. Direct installation on ceilings or walls, with cable entry at both ends and in the center. Through-wiring ensures quick and flexible connection. A robust and reliable IK07 and IP44 luminaire with a steel housing and aluminum end caps. Emergency lighting versions can be made upon request.

## Product- and environment images



# Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	113139 <b>Hurdal Maxi 1200 White 5610lm</b> <b>3000K Ra&gt;80 DALI-2</b> <b>38W LED</b> 148 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal	<b>Class I</b> <b>IP44</b> <b>IK07</b>	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1220 x W151 x H75
	113140 <b>Hurdal Maxi 1500 White 6980lm</b> <b>3000K Ra&gt;80 DALI-2</b> <b>47W LED</b> 149 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal	<b>Class I</b> <b>IP44</b> <b>IK07</b>	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1500 x W151 x H75
	113131 <b>Hurdal Maxi 1200 White 5610lm</b> <b>3000K Ra&gt;80 Trailing edge</b> <b>38W LED</b> 148 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal	<b>Class I</b> <b>IP44</b> <b>IK07</b>	Trailing edge	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1220 x W151 x H75
	113132 <b>Hurdal Maxi 1500 White 5620lm</b> <b>3000K Ra&gt;80 Trailing edge</b> <b>38W LED</b> 148 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal	<b>Class I</b> <b>IP44</b> <b>IK07</b>	Trailing edge	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1500 x W151 x H75
	113141 <b>Hurdal Maxi 1200 White 5870lm</b> <b>4000K Ra&gt;80 DALI-2</b> <b>38W LED</b> 154 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal	<b>Class I</b> <b>IP44</b> <b>IK07</b>	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1220 x W151 x H75
	113142 <b>Hurdal Maxi 1500 White 7330lm</b> <b>4000K Ra&gt;80 DALI-2</b> <b>47W LED</b> 156 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal	<b>Class I</b> <b>IP44</b> <b>IK07</b>	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1500 x W151 x H75

# Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	113133	<b>Class I</b>	Trailing edge	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1220 x W151 x H75
<b>Hurdal Maxi 1200 White 5870lm</b> <b>4000K Ra&gt;80 Trailing edge</b> <b>38W LED</b> 154 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal		<b>IP44</b>			
	113134	<b>Class I</b>	Trailing edge	Indoor 3-pole screwless terminal block with 3x2,5mm <sup>2</sup> through wiring	L1500 x W151 x H75
<b>Hurdal Maxi 1500 White 5880lm</b> <b>4000K Ra&gt;80 Trailing edge</b> <b>38W LED</b> 155 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal		<b>IP44</b>			
Accessories					
	820307				L137 x W27 x H27
	<b>Emergency battery 3 Hours 3.0Ah - Model No: B093</b>				