

Hurdal Maxi



Hurdal Maxi is a versatile surface-mounted luminaire that combines high performance with easy installation. The wide range of variants covers most needs, from general lighting to more advanced control solutions. Perfect for projects where quality, efficiency, and flexibility are essential. Direct installation on ceilings or walls, with cable entry at both ends and in the center. Through-wiring ensures quick and flexible connection. A robust and reliable IK07 and IP44 luminaire with a steel housing and aluminum end caps. Emergency lighting versions can be made upon request.

Hurdal Maxi






Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>113139 Hurdal Maxi 1200 White 5610lm 3000K Ra>80 DALI-2 38W LED 148 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	Class I IP44 IK07	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1220 x W151 x H75
 <p>113140 Hurdal Maxi 1500 White 6980lm 3000K Ra>80 DALI-2 47W LED 149 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	Class I IP44 IK07	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1500 x W151 x H75
 <p>113131 Hurdal Maxi 1200 White 5610lm 3000K Ra>80 Trailing edge 38W LED 148 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	Class I IP44 IK07	Trailing edge	Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1220 x W151 x H75
 <p>113132 Hurdal Maxi 1500 White 5620lm 3000K Ra>80 Trailing edge 38W LED 148 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	Class I IP44 IK07	Trailing edge	Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1500 x W151 x H75
 <p>113141 Hurdal Maxi 1200 White 5870lm 4000K Ra>80 DALI-2 38W LED 154 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	Class I IP44 IK07	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1220 x W151 x H75
 <p>113142 Hurdal Maxi 1500 White 7330lm 4000K Ra>80 DALI-2 47W LED 156 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	Class I IP44 IK07	DALI-2	Indoor 3-pole screwless terminal block with 3x2,5mm ² through wiring	L1500 x W151 x H75

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>113133 Hurdal Maxi 1200 White 5870lm 4000K Ra>80 Trailing edge 38W LED 154 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	<p>Class I IP44 IK07</p>	<p>Trailing edge</p>	<p>Indoor 3-pole screwless terminal block with 3x2,5mm² through wiring</p>	<p>L1220 x W151 x H75</p>
 <p>113134 Hurdal Maxi 1500 White 5880lm 4000K Ra>80 Trailing edge 38W LED 155 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Opal</p>	<p>Class I IP44 IK07</p>	<p>Trailing edge</p>	<p>Indoor 3-pole screwless terminal block with 3x2,5mm² through wiring</p>	<p>L1500 x W151 x H75</p>
Accessories				
 <p>820307 Emergency battery 3 Hours 3.0Ah - Model No: B093</p>				<p>L137 x W27 x H27</p>