

Rax Soft 220-240 Connect



Rax Soft 220-240 Connect is a flexible, high-performance downlight for public buildings, offices, corridors, and similar environments. It comes with an integrated SG Connect sensor for smart and energy-efficient lighting control. The sensor switches the light on when motion is detected and off after a defined time period, ensuring significant energy savings. It also features a built-in daylight sensor that can be activated to maintain the desired light level in its working area. Configuration is simple via the SG Connect Commissioning App, and the luminaire can be used as a standalone unit or as part of a larger system that can easily be expanded or reconfigured as needed. Rax Soft 220-240 Connect combines advanced optics with practical flexibility. It features optimized lens and reflector optics for excellent light control, and a satin matte reflector for maximum efficiency. The unique design allows installation in hole diameters from 220 to 240 mm and can be adapted to Ø200 mm holes with plate cut-out for the sensor box. The luminaire must be combined with a suitable driver kit according to the desired lumen output.

Rax Soft 220-240 Connect



Product- and environment images





Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212904 Rax Soft 220-240 Satin 3000K Ra>80 Connect LED SDCM:2 L90/B10>100,000 Beam: 62°, Direct, Satin Matt Reflector</p>	Class II SELV IP44/IP20	Connect	Recessed, Indoor Quick connector	Ø256 x H93
 <p>212905 Rax Soft 220-240 Satin 4000K Ra>80 Connect LED SDCM:2 L90/B10>100,000 Beam: 62°, Direct, Satin Matt Reflector</p>	Class II SELV IP44/IP20	Connect	Recessed, Indoor Quick connector	Ø256 x H93
Drivers				
 <p>820555 Driver kit Rax Soft Sensor 300mA Connect 12W 100,000</p>	Class II IP20	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L201 x W75 x H33
 <p>820556 Driver kit Rax Soft Sensor 500mA Connect 19W 100,000</p>	Class II IP20	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L201 x W75 x H33
 <p>820557 Driver kit Rax Soft Sensor 700mA Connect 27W 100,000</p>	Class II IP20	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L201 x W75 x H33
 <p>820558 Driver kit Rax Soft Sensor 900mA Connect 35W 100,000</p>	Class II IP20	Connect	Recessed, Indoor 3 pol Linect / screwless terminal block	L201 x W75 x H33

Accessories

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 900109 Reliefplate Weight distribution panel				L400 x W400 x H1
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35