

Nano Tilt



Small downlight with polished reflector for windows, cabinets and niches to give a nice moodful light. Nano Tilt, which can be directed, has a 36 degree spread angle. Delivered without driver. Nanodriver (optional) with max 9W dimmed with 1-10V / Impuls DIM, max 17W dimmed with Trailing edge dimming / Impuls DIM and max 4,2W dimmed with Trailing edge dimming.

Nano Tilt









Product- and environment images






Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>907019</p> <p>Nano Tilt Black In/out 240lm 2700K</p> <p>Ra>90 Driver 350mA ordered separately</p> <p>4W LED</p> <p>60 lm/W SDCM:2</p> <p>L70/B50>50,000</p> <p>Beam: 36°, Direct, Reflector medium</p>	<p>Class III</p> <p>IP65</p>	<p>Driver 350mA</p> <p>ordered separately</p>	<p>Recessed, Indoor / Outdoor</p>	<p>Ø48 x H29</p>
 <p>907016</p> <p>Nano Tilt White In/out 240lm 2700K</p> <p>Ra>90 Driver 350mA ordered separately</p> <p>4W LED</p> <p>60 lm/W SDCM:2</p> <p>L70/B50>50,000</p> <p>Beam: 36°, Direct, Reflector medium</p>	<p>Class III</p> <p>IP65</p>	<p>Driver 350mA</p> <p>ordered separately</p>	<p>Recessed, Indoor / Outdoor</p>	<p>Ø48 x H29</p>
 <p>907020</p> <p>Nano Tilt Black In/out 240lm 3000K</p> <p>Ra>90 Driver 350mA ordered separately</p> <p>4W LED</p> <p>60 lm/W SDCM:2</p> <p>L70/B50>50,000</p> <p>Beam: 36°, Direct, Reflector medium</p>	<p>Class III</p> <p>IP65</p>	<p>Driver 350mA</p> <p>ordered separately</p>	<p>Recessed, Indoor / Outdoor</p>	<p>Ø48 x H29</p>
 <p>907017</p> <p>Nano Tilt White In/out 240lm 3000K</p> <p>Ra>90 Driver 350mA ordered separately</p> <p>4W LED</p> <p>60 lm/W SDCM:2</p> <p>L70/B50>50,000</p> <p>Beam: 36°, Direct, Reflector medium</p>	<p>Class III</p> <p>IP65</p>	<p>Driver 350mA</p> <p>ordered separately</p>	<p>Recessed, Indoor / Outdoor</p>	<p>Ø48 x H29</p>
 <p>907013</p> <p>Nano Tilt White 270lm 4000K</p> <p>Ra>90 Driver 350mA ordered separately</p> <p>4W LED</p> <p>68 lm/W SDCM:2</p> <p>L70/B50>50,000</p> <p>Beam: 36°, Direct, Reflector medium</p>	<p>Class III</p> <p>IP44</p>	<p>Driver 350mA</p> <p>ordered separately</p>	<p>Recessed, Indoor</p>	<p>Ø48 x H29</p>
 <p>907018</p> <p>Nano Tilt White In/out 270lm 4000K</p> <p>Ra>90 Driver 350mA ordered separately</p> <p>4W LED</p>	<p>Class III</p> <p>IP65</p>	<p>Driver 350mA</p> <p>ordered separately</p>	<p>Recessed, Indoor / Outdoor</p>	<p>Ø48 x H29</p>
<p>Drivers</p>				

Article codes



Article	68 lm/W SDCM:2	Protection	Control gear	Mounting/Connection	Dimensions
 L70/B50>50.000 Beam: 36° Direct Reflector medium	820078 Nano White Driver 4.2W 350mA Trailing edge	IP20	Trailing edge	Indoor	Ø23 x L90 x W23 x H19
	820091 Nano White Driver 17W 350mA Trailing edge / Push Dim 17W	IP20	Trailing edge / Push Dim	Indoor	L166 x W46 x H34
Accessories					
	9228 Nano Tilt White 67mm Rehabring				L67 x W67 x H3