

Lyskilder E27



Dimbar E27 LED-lyskilde med 5 års systemgaranti ved bruk sammen med SG-armatur.

Lyskilder E27



Produkt- og miljøbilder



Artikkel	Beskyttelse	Styring	Montering/Tilkobling	Dimensjoner
10W				
 3800059 E27 820lm 3000K Ra>90 10W 82 lm/W SDCM:4 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø60 x L121
 3800500 E27 806lm 2700K Ra>90 10W 81 lm/W SDCM:6 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø60 x L110
 3815500 E27 LED DimToWarm 806lm 2000-2800K Ra>80 10W 81 lm/W SDCM:6 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø60 x L110
15W				
 3800112 E27 LED Hvit 1200lm 2700K Ra>90 15W 80 lm/W SDCM:3 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø95 x L136
 3800113 E27 LED Hvit DimToWarm 1200lm 2000-2800K Ra>80 15W 80 lm/W SDCM:6 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø95 x L135
 3800114 E27 LED Hvit 1200lm 3000K Ra>90 15W 80 lm/W SDCM:3 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø95 x L136
4W				

Artikkel	Beskyttelse	Styring	Montering/Tilkobling	Dimensjoner
 3800505 E27 E27 Filament 545lm 2700K Ra>80 4W LED 136 lm/W SDCM:6 L70/B50>15.000 Direkte,		Faseavsnitt		Ø70 x L125
5W				
 3800117 E27 LED Hvit DimToWarm 350lm 2000-2800K Ra>80 5W 70 lm/W SDCM:6 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø45 x L79
6W				
 3800125 E27 LED E27 450lm 2700K Ra>90 6W 75 lm/W SDCM:3 L70/B50>50.000 Lysspredning: 190°, Direkte,		Faseavsnitt		Ø60 x L110