



Design: Christian Hvidt. . Light for mounting on mast or wall lamp (680mm in diameter) is IP65-rated. Luminaire body, wall bracket and top made of die-cast aluminium, reflector and truncated cone made of polycarbonate. Powder-coated dark grey luminaire body, wall bracket and top. Reflector, inside of cone and top in special reflector-white colour. Reflector and optics are particularly well suited to giving a direct, direct/indirect, indirect or direct/asymmetrical light distribution via a clear or opal truncated cone. Complete with connection for operation of LED light sources mounted to component rail with connector system and pre-mounted with five-metre connection cable. Lamp head prepared for mounting on 60 mm or 108 mm mast. Electrical safety class II.

# Ray 680



## Produkt- og miljøbilder



Artikkel		Beskyttelse	Styring	Montering/Tilkobling	Dimensjoner
	3500355	<b>Klasse I</b>	Ikke dimbar	Mast - topp (Ø60mm), Outdoor	Ø680 x H703
	<b>Ray 680 D/I LED Grå 2990lm 3000K</b>	<b>IP65</b>		Kabel 3x1mm <sup>2</sup> 5,0m	
	<b>Ra&gt;80 Ikke dimbar</b>	<b>IK10</b>			
	<b>24W LED</b>				
	125 lm/W SDCM:2				
	L90/B10>100.000				
	Direkte/Indirekte 85/15%, Opal				