Arena

Electrical System wattage:

Voltage:

Arena 1200 White Narrow 23530lm 4000K Ra>80 On/Off

Article code: EAN:

Max. luminaires per circuit breaker:

8246093909 5703821176392

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



140W 220-240V B10: 5, B16: 8, C10: 8, C16: 13

Light technic	
Type of light source:	LED
Luminous flux:	23530lm
Efficacy:	168 lm/W
Colour temperature:	4000K
Colour rendering (Ra):	Ra>80
MacAdams factor:	SDCM: 3
Lifetime:	L90/B10>70,000
Lifetime:	L80/B20>100,000
Minimum ambient temperature:	-25°C
Light distribution:	Direct
Optic:	Lens Narrow
Beam angle:	Narrow
UGR:	UGR<16
Control/Dimming	
Туре:	On/Off
Protection	
Luminaire class:	Class I
IK Class:	IK08
IP Class:	IP23
Energy and approvals	
Contains light source of energy class:	С
Breeam:	Fulfils Hea 01 for flicker free lighting
Materials and finish	
Housing:	Sheet steel
Colour:	White (RAL 9010, 20% gloss)
Optics:	Acrylic (PMMA)

Mounting/Connection Suspended or surface, Indoor 1200 5-pole screwless terminal block with 5x2,5mm2 through wiring

Dimensions	
Length (mm) L:	1256
Width (mm) W:	295
Height (mm) H:	57
Weight (kg) gross/net:	8.2 / 8

Packaging

Mounting:

Connection:

Module:

Packing dimensions (mm):

1285 x 300 x 65











