

Bassi Black 690lm 3000K Ra>80 Sensor

Article code: 614189  
EAN: 7021986141894



• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 11W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light technic

Type of light source: LED  
Luminous flux: 690lm  
Efficacy: 63 lm/W  
Colour temperature: 3000K  
Colour rendering (CRI): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L70/B50>50,000  
Light distribution: Direct  
Optic: Opal  
Beam angle: 120°  
Photobiological safety: RG 0

Control/Dimming

Type: Sensor

Protection

Luminaire class: Class II  
IK Class: IK10  
IP Class: IP65  
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C  
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium  
Colour: Black (RAL 9004)  
Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor / Outdoor  
Connection: Screwless terminal block

Dimensions

Length (mm) L: 240  
Width (mm) W: 240  
Height (mm) H: 80  
Weight (kg) gross/net: 1.8 / 1.8

Packaging

Packing dimensions (mm): 240 x 240 x 80

