
Callisto Wall

Callisto Wall White 120lm 3000K Ra>80 Trailing edge dimming

Article code: 912015
EAN: 7021989120155

IP65 IK06





Electrical

System wattage:	3W
Voltage:	220-240V
Max. luminaires per circuit breaker:	B10: 115, B16: 184, C10: 134, C16: 215

Light technic

Type of light source:	LED
Luminous flux:	120lm
Efficacy:	40 lm/W
Colour temperature:	3000K
Colour rendering (CRI):	Ra>80
MacAdams factor:	SDCM: 3
Lifetime:	L70/B50>50,000
Light distribution:	Direct/Asymmetric
Optic:	Glass Clear
Beam angle:	70°/40°

Control/Dimming

Type:	Trailing edge dimming

Protection

Luminaire class:	Class II

Energy and approvals

Contains light source of energy class:	F
Breeam:	Fulfils Hea 01 for flicker free lighting
BVB:	Yes

Materials and finish

Housing:	Aluminium
Colour:	Matte white (RAL 9003)
Optics:	Tempered glass

Mounting/Connection


Mounting:	Surface, Indoor / Outdoor
Connection:	Screwless terminal block

Dimensions

Height (mm) H:	35
Diameter (mm) D:	110
Weight (kg) gross/net:	0.3 / 0.238

Packaging

Packing dimensions (mm):	120 x 115 x 45



7 0 2 1 9 8 9 1 2 0 1 5 5