## CircLED Multi



## CircLED Multi Black Lens 2, Class II Top 3120lm 4000K Ra>70 On/Off

Article code: 8246084565 FAN: 5703821165914

= This article is produced by order, with an expected delivery time of 3-4 weeks.







Electrical

System wattage: 23W Voltage: 220-240V Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

LED Type of light source: Luminous flux: 3120lm Efficacy: 136 lm/W Colour temperature: 4000K Colour rendering (Ra): Ra>70 MacAdams factor: SDCM: 3 Lifetime: L80/B10>100,000 Light distribution: Multi Lens Optic: Lens ULOR ( Yes / Yes, up to 17° tilt angle

Control/Dimming

On/Off Type:

**Protection** 

Luminaire class: Class II IK Class: IK09 IP66 IP Class: Integrated surge protection: Integrated (min. 4 kV)

**Energy and approvals** 

Contains light source of energy class: C Fulfils Hea 01 for flicker free lighting Breeam:

Materials and finish

Housing: Die-cast aluminium Colour: Black (20% gloss) Optics: Tempered glass

**Mounting/Connection** 

Mounting: Post - top (Ø60mm), Outdoor Cable 2x1mm<sup>2</sup> 6m Cable: Wind projected area: 0,0415m<sup>2</sup> - Max 6,2 kg

**Dimensions** 

Length (mm) L: 460 Width (mm) W: 390 Height (mm) H: 185 Weight (kg) gross/net: 8.2/8

**Packaging** 

Packing dimensions (mm): 525 x 395 x 210

**Explanatory text** 

Class II











