CircLED Single

Electrical

Packaging



CircLED Single Grey Top Adjustable 5-17° 1640lm 4000K Ra>80 On/Off

Article code: 8246084468 EAN: 5703821165822

= This article is produced by order, with an expected delivery time of 3-4 weeks.





System wattage: 14W Voltage: 220-240V Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic LED Type of light source: Luminous flux: 1640lm Efficacy: 117 lm/W Colour temperature: 4000K Colour rendering (CRI): Ra>80 MacAdams factor: SDCM: 2 L90/B10>100,000

Light distribution: Single Lens Optic: Lens

Control/Dimming Type: On/Off

Protection Luminaire class: Class II

Energy and approvals Contains light source of energy class: D Fulfils Hea 01 for flicker free lighting Breeam:

Materials and finish Housing: Die-cast aluminium Colour: Grey (structure 2150 sablé) Optics: Tempered glass

Mounting/Connection Post - adjustable head 5-17°, Outdoor Mounting: Cable: Cable 2x1mm² 6m Wind projected area: 0,0415m² - Max 6,2 kg

Dimensions Length (mm) L: 460 390 Width (mm) W: Height (mm) H: 185 Weight (kg) gross/net: 8.2/8

Packing dimensions (mm): 525 x 395 x 210











