

CircLED Single Black Top 2430lm 4000K Ra>80 On/Off

Article code: 8246084497
 EAN: 5703821165853



• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 21W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
 Luminous flux: 2430lm
 Efficacy: 116 lm/W
 Colour temperature: 4000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 2
 Lifetime: L90/B10>100,000
 Light distribution: Single Lens
 Optic: Lens

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class II

Energy and approvals

Contains light source of energy class: D
 Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Die-cast aluminium
 Colour: Black (20% gloss)
 Optics: Tempered glass

Mounting/Connection

Mounting: Post - top (Ø60mm), Outdoor
 Cable: Cable 2x1mm² 6m
 Wind projected area: 0,0415m² - Max 6,2 kg

Dimensions

Length (mm) L: 460
 Width (mm) W: 390
 Height (mm) H: 185
 Weight (kg) gross/net: 8.2 / 8

Packaging

Packing dimensions (mm): 525 x 395 x 210

