## CircLED Single



## CircLED Single Grey Side 3320lm 4000K Ra>80 On/Off

Article code: 8246086178 EAN: 5703821166379

= This article is produced by order, with an expected delivery time of 3-4 weeks.







**(€** □ IP66 IK09

Electrical

System wattage: 30W Voltage: 220-240V Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

LED Type of light source: Luminous flux: 3320lm Efficacy: 111 lm/W Colour temperature: 4000K Colour rendering (CRI): Ra>80 MacAdams factor: SDCM: 2 L90/B10>100,000 Light distribution: Single Lens Optic: Lens

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class II

**Energy and approvals** 

Contains light source of energy class: D Fulfils Hea 01 for flicker free lighting Breeam:

Materials and finish

Housing: Die-cast aluminium Colour: Grey (structure 2150 sablé) Optics: Tempered glass

**Mounting/Connection** 

Pole - Side (Ø48mm), Outdoor Mounting: Cable: Cable 2x1mm<sup>2</sup> 10m Wind projected area: 0,0415m<sup>2</sup> - Max 6,2 kg

**Dimensions** 

Length (mm) L: 523 Width (mm) W: 390 135 Height (mm) H: Weight (kg) gross/net: 8.2/8

**Packaging** 

Packing dimensions (mm): 525 x 395 x 210











