

Curve Direct Graphite 530lm 2700K Ra>80 Trailing edge dimming

Article code: 611398
 EAN: 7021986113983
 Replaces: 623365




Electrical

System wattage: 7W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 15, B16: 25, C10: 31, C16: 50



Light technic

Type of light source: LED
 Luminous flux: 530lm
 Efficacy: 76 lm/W
 Colour temperature: 2700K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B10>50,000
 Light distribution: Direct
 Optic: Glass Frosted
 Visible flicker (PstLM): 0.06
 Stroboscopic flicker (SVM): 0.38



Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I

Energy and approvals

Contains light source of energy class: E
 Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
 Colour: Graphite
 Optics: Tempered glass

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
 Connection: Screwless terminal block

Dimensions

Width (mm) W: 320
 Height (mm) H: 60
 Depth (D): 103
 Weight (kg) gross/net: 1.54 / 1.4

Packaging

Packing dimensions (mm): 330 x 120 x 70

