Curve Direct



Curve Direct Graphite 320lm 3000K Ra>80 Trailing edge dimming

Article code: 623366

EAN: 7021986233667

CE IP65 IK06 A

Electrical

System wattage: 10W Voltage: 220-240V Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Type of light source: **Discontinued**

LED
Luminous flux: 320lm

Efficacy: 32 lm/W

Colour temperature: 3000K

Colour rendering (CRI): Ra>80

MacAdams factor: SDCM: 3

Lifetime: L70/B10>50,000

Light distribution: Direct

Optic: Glass Clear

Beam angle: 110°

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I IK Class: IK06 IP Class: IP65

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium Colour: Graphite Optics: Tempered glass

Mounting/Connection

Mounting: Surface, Indoor / Outdoor Connection: Screwless terminal block

Dimensions

 Width (mm) W:
 320

 Height (mm) H:
 60

 Depth (D):
 103

 Weight (kg) gross/net:
 1.68 / 1.4

Packaging

Packing dimensions (mm): 330 x 120 x 70











